




**HiChem Industries Pty Ltd.**  
73 Hallam South Road Hallam, Vic 3803  
Phone (03) 9796 3400 Fax (03) 9796 4500  
ACN 006-542-767



## PRODUCT INFORMATION SHEET

z:\public\prodinfo\misc\ fa.doc 25-4-98

# FLEXI ADD

### Description

*MOTOSPRAY FLEXI ADD* is a specialised additive used to increase the flexibility of automotive acrylic topcoats.

### Uses

Added to acrylic lacquers when used to paint flexible plastic car body parts.

Use with *MOTOSPRAY ACRYLIC LACQUERS* including solid colours, monometallics, Clear Over Base, Top Coat Clear, High Opacity White, Jet Black, and Satin Black.

### Surface Preparation

Thoroughly clean surface with Prepwash. Apply *MOTOSPRAY FLEXI PRIME* as directed.

### Additive Addition

Add *MOTOSPRAY FLEXI ADD* to the *ACRYLIC LACQUER* in the following proportions:-

Hard Plastics:	5% addition, up to maximum of 10%
Flexible Plastics:	10% addition, up to maximum of 15%

### Paint Application

Add the appropriate amount of required thinner to the Acrylic Lacquer and Flexi-Add mixture and spray in light single coats.

### Storage

Store in a cool dry place. Always replace the lid securely after use.

### Safety

Flammable liquid. Provide adequate ventilation during use.  
See material safety data sheet.

### Standard Packages and Product Codes

250 mls	FA250
---------	-------

*The information contained in this bulletin is presented in good faith based on thorough laboratory and field testing but without warranty. As we have no control over the conditions under which these products are used, it is recommended that all products be tested by the end user to ensure the suitability of the product for the particular application and conditions.*