



**HiChem Industries Pty Ltd.**  
73 Hallam South Road Hallam, Vic 3803  
Phone (03) 9796 3400 Fax (03) 9796 4500  
ACN 006-542-767



## PRODUCT INFORMATION SHEET

G:\PRODINFO\BODYFILR\SBOG.DOC 03/07/98 14:05

# SUPERBOG

### Description

*MOTOSPRAY SUPER BOG* is a light weight polyester 2 pack repair filler.

### Uses

For the repair of dents in car bodies, boats, tanks etc. Excellent adhesion to aluminium, fibreglass, steel and wood.

### Properties

- \* Easy to sand and file
- \* Easy to mix and apply
- \* Superb adhesion properties
- \* Colour - light blue

### Surface preparation

Clean and roughen surface by sanding or grinding. Remove all dust, oil, grease, wax, paint and rust to leave a clean bare metal surface.

### Application

Mix 50 parts *SUPER BOG* to 1 part hardener. Measure reasonably carefully as an excess of peroxide hardener can bleed through to topcoat and cause discoloration. Mix carefully with a wide bladed spatula. Take care not to mix in air bubbles. The mixture is ready for use when a uniform colour is obtained. Apply thinly and evenly, avoid air bubbles. If required a second coat may be applied after the first coat has gelled.

### Drying times

Setting time ("Gel Time") - approximately 6 minutes at 20°C sanding and finishing may be commenced 20-30 minutes after application. Allow longer in cooler weather. Gel time is affected by temperature. Do not use this product if temperature is less than 5°C.

### Storage

Store in a cool dry place. Always replace the lid securely after use.

### Shelf life

12 months in sealed full containers

### Safety

See material safety data sheet

### Standard packages and product codes

4.0KG                      SBOG4

*The information contained in this bulletin is presented in good faith based on thorough laboratory and field testing but without warranty. As we have no control over the conditions under which these products are used, it is recommended that all products be tested by the end user to ensure the suitability of the product for the particular application and conditions.*