



**HiChem Industries Pty Ltd.**  
73 Hallam South Road Hallam, Vic 3803  
Phone (03) 9796 3400 Fax (03) 9796 4500  
ACN 006-542-767



## PRODUCT INFORMATION SHEET

G:\SECURE\Product Information\DETAIL\Machine Grade 10-5-06.doc

# MACHINE GRADE CUTTING COMPOUND

### Description:

*Motospray Machine Grade Cutting Compound* is a heavy duty cutting compound for use with an electric or air powered buffing machine fitted with a lambs wool bonnet or sponge pad. It may be hand rubbed on small areas only.

### Uses:

For removing imperfections such as overspray and orange peel on newly painted surfaces and for restoring gloss to chalked or dull surfaces.

Designed primarily for use with automotive acrylic lacquers. Use on *Motospray Acrylic Lacquer* tint system colours, factory *Acrylic Solid Colours*, *High Opacity White*, *Jet Black*, *Top Coat Clear*, *2 Pack Iso-Free Finish Colours* and *2 Pack Iso-Free Clear*.

Do not use on 2 pack urethanes (eg *HiChem 2 Pack Colours* or *Clears*), air dry enamels or any type of satin or matt finish.

Also suitable for other paints-see the paint label or Product Information Sheet for details.

### Properties:

- Excellent cutting qualities
- Thick green coloured paste
- Easily washed off with water
- May be thinned with water

### Surface Preparation:

Wash the whole surface to be cut with *Motospray Truck & Carwash*. Some surfaces may be sanded with 1500-2000 grit Wet & Dry paper to remove imperfections. Refer to the Product Information Sheet for the particular paint for detailed instructions.

### Application:

Machine buffing, electric or air powered. Apply a small amount to the surface with a brush, disperse into lambswool bonnet or sponge pad with machine off. Turn machine on. Do not apply pressure, keep the buff moving across the surface to avoid burning the finish or rub-throughs on edges. Keep the surface wet by occasionally applying fine water spray.

### Hand Rubbing:

Apply to a soft, clean and damp cloth. Use firm pressure and rub in one direction only.  
For use on small areas only.

### Clean up:

Remove all residue with *Motospray Truck & Carwash*. Buff Pad may be washed with warm soapy water.

### Storage:

Store in a cool dry place. Always replace the lid securely after use.

### Safety:

See Material Safety Data Sheet.

### Standard Packages:

500gram.	MG500	1 kg.	MG1
5 kg.	MG5	17 kg.	MG17

*The information contained in this bulletin is presented in good faith based on thorough laboratory and field testing but without warranty. As we have no control over the conditions under which these products are used, it is recommended that all products be tested by the end user to ensure the suitability of the product for the particular application and conditions.*