



HiChem Industries Pty Ltd.
73 Hallam South Road Hallam, Vic 3803
Phone (03) 9796 3400 Fax (03) 9796 4500
ACN 006-542-767



PRODUCT INFORMATION SHEET

z:\public\prodinfo\detail\ns.doc 4-4-98

NON-SILICONE AUTO POLISH

Description

MOTOSPRAY NON-SILICONE AUTO POLISH is a light duty polish used to restore slightly dulled or damaged surfaces to a brilliant lustre.

Uses

NON-SILICONE AUTO POLISH is used to restore gloss to dulled and damaged surfaces. It will remove oxidised surface layers of paint, shallow scratches and marks caused by parking scrapes, tree sap, and bird droppings.

NON-SILICONE AUTO POLISH can be used on all finishes including Acrylic, Enamels and Fibreglass.

Note: For badly weathered surfaces, deeper scratches and imperfections we recommend *MOTOSPRAY QUICKCUT* as a medium duty cut and polish, and *MOTOSPRAY MACHINE GRADE CUTTING COMPOUND* for heavy cutting.

Surface Preparation

Remove dirt and grime from the surface with *MOTOSPRAY CARWASH* or *TRUCK AND CAR WASH* and allow to dry.

Application

Shake well and apply *NON-SILICONE AUTO POLISH* evenly with a soft cloth rubbing briskly.

Buff with a clean, soft cloth until dry and all residue is removed.

Note: Do not use on hot surfaces

Storage

Store in a cool dry place. Always replace the lid securely after use.

Safety

See material safety data sheet.

Standard Packages and Product Codes

500 ml	NS500
4 litre	NS4
20 litre	NS20

The information contained in this bulletin is presented in good faith based on thorough laboratory and field testing but without warranty. As we have no control over the conditions under which these products are used, it is recommended that all products be tested by the end user to ensure the suitability of the product for the particular application and conditions.