



HiChem Industries Pty Ltd.
73 Hallam South Road Hallam, Vic 3803
Phone (03) 9796 3400 Fax (03) 9796 4500
ACN 006-542-767



PRODUCT INFORMATION SHEET

z:\public\prodinfo\detail\qc.doc 4-4-98

QUICK CUT

Description

MOTOSPRAY QUICK CUT is an easily applied cutting and polishing compound which revitalises dull and weathered surfaces.

Uses

QUICK CUT removes grime and oxidised paint. It is suitable for removing minor scratches and imperfections such as those left by tree sap, bird droppings and car park scrapes. It may also be used to remove overspray and minor surface defects after spray painting.

QUICK CUT is a medium strength cutting compound. For heavier cutting use *MOTOSPRAY MACHINE GRADE CUTTING COMPOUND* or *SUPERDUTY RUBBING COMPOUND*.

Properties

Colour - Beige

Features -

- Easily applied by hand rubbing or machine buffing.
- Easily polished off.

Surface Preparation

Wash and dry car.

Application

1. Shake bottle and apply evenly with a soft open weave cloth, in a circular motion covering an area about 25cm at a time.
2. Continue to apply until entire panel is covered, then wipe off with a clean soft cloth.
3. Once surface has been restored, use *MOTOSPRAY NON-SILICONE AUTOPOLISH* to remove any swirl marks and to obtain a bright highly polished finish.

Note : May also be applied via a lambswool pad and polishing machine.

Storage

Store in a cool dry place. Always replace the lid securely after use.

Safety

See material safety data sheet.

Standard Packages and Product Codes

500 mls

QC500

The information contained in this bulletin is presented in good faith based on thorough laboratory and field testing but without warranty. As we have no control over the conditions under which these products are used, it is recommended that all products be tested by the end user to ensure the suitability of the product for the particular application and conditions.