



HiChem Industries Pty Ltd.
73 Hallam South Road Hallam, Vic 3803
Phone (03) 9796 3400 Fax (03) 9796 4500
ACN 006-542-767



PRODUCT INFORMATION SHEET

z:\public\prodinfo\detail\sc.doc 4-4-98

SUPREME CUT

Description:

MOTOSPRAY SUPREME CUT is a heavy duty cutting compound for use with an electric or air powered buffing machine fitted with a lambswool bonnet. It may be hand rubbed on small areas only.

Uses:

For removing overspray and orange peel on new surfaces and restores gloss to chalked or dull surfaces. May be used with acrylic or two pack paints.

Properties:

- Excellent cutting qualities
- Thick beige coloured paste
- Easily washed off with water
- May be thinned with water

Surface Preparation:

Wash the whole surface to be cut with *MOTOSPRAY CARWASH* or *MOTOSPRAY TRUCK AND CARWASH*.

Application:

Machine buffing, electric or air powered. Apply a small amount to the surface with a brush, disperse into lambswool bonnet with machine OFF. Turn on machine. Do not apply pressure, keep the buff moving across the surface to avoid burning the finish or rub-throughs on edges.

Hand Rubbing:

Apply to a soft, clean and damp cloth. Use firm pressure and rub in one direction only. For use on small areas only.

Clean up:

Remove all residue with *MOTOSPRAY CARWASH*. Buff Pad may be washed with warm soapy water.

Storage:

Store in a cool dry place. Always replace the lid securely after use.

Safety:

See Material Safety Data Sheet.

Standard Packages:

2.5 kg. SC2.5

The information contained in this bulletin is presented in good faith based on thorough laboratory and field testing but without warranty. As we have no control over the conditions under which these products are used, it is recommended that all products be tested by the end user to ensure the suitability of the product for the particular application and conditions.