



HiChem Industries Pty Ltd.
73 Hallam South Road Hallam, Vic 3803
Phone (03) 9796 3400 Fax (03) 9796 4500
ACN 006-542-767



PRODUCT INFORMATION SHEET

z:\public\prodinfo\hardware \ gip.doc 25-4-98

GALVANISED IRON PRIMER

Description

HiChem Galvanised Iron Primer is a quick drying, premium quality water based primer for all types of galvanised metal surfaces. It contains anticorrosion pigments to give maximum protection.

Uses

Suitable substrates include galvanised surfaces such as sheet metal structural steel, roofing, guttering, garden sheds, garages and water tanks.

Surface Preparation

Remove rust and any loose and flaking paint. Ensure surface is free from grease, oil and dirt. New unpainted surfaces need no chemical pretreatment or the traditional weathering period before painting.

Application

Apply one full coat directly from the can. May be applied by brush or roller. Finish coat may be applied after a drying period of 2 hours. Suitable finish coats include enamels and water based exterior acrylics. **Do not** use this product if temperature is below 10°C.

Thinning

Not required

Clean up

Wash all equipment with water

Drying time

Touch dry in 30 minutes at 20°C.

Recoat time - 2 hours at 20°C

Coverage

Approximately 16 square metres per litre

Colours

Yellow only

Standard packages and Product Codes

4 litre	=	GIP4
1 litre	=	GIP1
500 mls	=	GIP500

The information contained in this bulletin is presented in good faith based on thorough laboratory and field testing but without warranty. As we have no control over the conditions under which these products are used, it is recommended that all products be tested by the end user to ensure the suitability of the product for the particular application and conditions.