



HiChem Industries Pty Ltd.
73 Hallam South Road Hallam, Vic 3803
Phone (03) 9796 3400 Fax (03) 9796 4500
ACN 006-542-767



PRODUCT INFORMATION SHEET

z:\public\prodinfo\hardware\PSW.doc 15-12-98

ACRYLIC PRIMER SEALER

Description

HICHEM ACRYLIC PRIMER SEALER is a quick drying water based primer and sealer for interior surfaces. Its formulation provides excellent hiding power and adhesion and is applied in an easy one coat application.

Uses

ACRYLIC PRIMER SEALER is suitable for plaster, masonry, paperfaced wallboard, timber, MDF, and can be used under water or oil based top coats.

Surface Preparation

Previously painted surfaces - Scape off loose and flaking paint and wash with sugar soap. Fill cracks and nail holes with suitable wood filler. Sand smooth and dust off. Sand Gloss and Semigloss surfaces thoroughly and wipe clean.

New surfaces - Brick, plaster, masonry, paperfaced wallboard and timber surfaces. Fill cracks and nail holes with a suitable filler. Sand smooth and dust off.

Thinning

ACRYLIC PRIMER SEALER is supplied ready for use for brushing or rolling, however if surface is very porous or under hot conditions use 100ml of water per litre.

For spraying up to 15% water may be added depending on spray setup.

Application

Stir contents thoroughly before use.

Apply 1-2 coats of *ACRYLIC PRIMER SEALER* by spray, brush or roller.

Drying time

Under normal conditions - touch dry in 20 minutes and can be recoated after 2 hours.

Coverage

Approx. 15 square metres per litre

Clean up

Use water.

Storage

Store in a cool dry place. Always replace the lid securely after use.

Safety

Provide adequate ventilation during use. See material safety data sheet.

Standard Packages and Product Codes

500 ml	PSW500
1 Litre	PSW1
4 Litre	PSW4
20 Litre	PSW20

The information contained in this bulletin is presented in good faith based on thorough laboratory and field testing but without warranty. As we have no control over the conditions under which these products are used, it is recommended that all products be tested by the end user to ensure the suitability of the product for the particular application and conditions.