




**HiChem Industries Pty Ltd.**  
73 Hallam South Road Hallam, Vic 3803  
Phone (03) 9796 3400 Fax (03) 9796 4500  
ACN 006-542-767



## PRODUCT INFORMATION SHEET

G:\SECURE\Product Information\MISC\RUST CONVERTER.doc 6-4-01

# RUST CONVERTER & PRIMER/SEALER

### Description:

*MOTOSPRAY RUST CONVERTER & PRIMER/SEALER* is a rust converter with primer/ sealer built in. In one step it **chemically reacts with rust**, converting it to a hard inert organic compound, and then **seals the surface** with an impervious coating. This coating is a suitable base for a variety of paint systems including automotive acrylics, Enamels, 2 Pack and waterbased.

### Uses:

Recommended for the treatment of rust on steel and galvanised surfaces whenever it is not practical to remove the existing rust completely.

Many applications: Interior or exterior, Household, Automotive, Marine, Industrial, Agricultural. Gutters and roofing, garden furniture, steel fencing and gates, motor vehicles, trailers, caravans, machinery, equipment, bicycles, toys, electrical appliances and much more.

### Properties:

- Easy to use.
- Non toxic, non hazardous.
- Converts rust and primes in one application.
- Can be applied to dry or damp rusted surfaces.
- No washing down after application.
- Does not contain Phosphoric Acid.

### Suitable Substrates:

Lightly rusted steel, galvanised steel and related products such as zinc-alum and Duragal. Will also bond to a variety of surfaces which may be attached to the rusted part. For example timber, aluminium, Stainless Steel, new galvanised steel, bare steel, and various paints such as HiChem Cold Gal and Quick Dry Enamel.

### Surface Preparation:

Remove loose and heavy rust by means such as wire brushing. Wash off any dust, salt, chemical, grease, oil or other contaminants. Wash with a suitable degreaser ( eg Motospray Degrease) or detergent ( eg Motospray Car Wash or Truck and Car Wash). Rinse with clean water.

### Application:

Mix by shaking the bottle vigorously.

Pour *RUST CONVERTER and PRIMER/SEALER* into a plastic container. Pour only enough for the job and don't return leftover *RUST CONVERTER* to the bottle.

Brush or roll a liberal coating of *RUST CONVERTER and PRIMER/SEALER* over the rusted surface (2 coats, if required, for maximum durability; allow 3 hours drying between coats). May be applied to damp but not wet surfaces. Do not apply to hot surfaces.

The rusted areas of the surface will turn predominantly black.

### Finishing:

Do not sand *RUST CONVERTER and PRIMER/SEALER* .If a smooth surface is required apply a suitable sandable primer.

Suitable for use under most paint systems.

May be left up to 3 months before priming and topcoating.

Ensure *RUST CONVERTER and PRIMER/SEALER* is thoroughly dry before applying topcoats. With single pack paints allow minimum drying 3 hours at 20°C before applying primers or topcoats. For 2 pack paints allow a minimum 24 hours drying at 20°C.

**Clean Up:**

Immediately after painting, clean brushes, equipment and small spills with water and detergent. For dried material clean with Superglow Multipurpose Thinner.

**Coverage:**

5-10 square metres per litre

**Precautions:**

Only apply to rusted surfaces-not a rust preventative for clean steel.  
Staining may occur if over coated with light coloured or water based topcoats or primers.

**Storage:**

Store in a cool position. Reseal container after use. Do not return leftover paint to container.

**Safety:**

Non Flammable, Non Toxic. Wear gloves and goggles. See Material Safety Data Sheet for further details.

**Standard Packages and Product codes:**

250mls                  RC250

*The information contained in this bulletin is presented in good faith based on thorough laboratory and field testing but without warranty. As we have no control over the conditions under which these products are used, it is recommended that all products be tested by the end user to ensure the suitability of the product for the particular application and conditions.*