



HiChem Industries Pty Ltd.
73 Hallam South Road Hallam, Vic 3803
Phone (03) 9796 3400 Fax (03) 9796 4500
ACN 006-542-767



PRODUCT INFORMATION SHEET

z:\public\proinfo\misc\ sil.doc 2-5-98

ANTI-SILICONE DROPS

Description

MOTOSPRAY ANTI-SILICONE DROPS is a special paint additive designed to overcome minor wet paint film defects.

Uses

ANTI-SILICONE DROPS act by improving the levelling of the wet paint film. It can be used to overcome the effects of surface and airborne contamination such as silicon or oil. Suitable for use in solvent based coatings such as *HICHEM QUICK DRY ENAMEL*, *MOTOSPRAY ACRYLIC LACQUER* and *MOTOSPRAY AUTO-ENAMEL*. Do not use in 2 Pack coatings.

Properties

Colour - clear

Surface Preparation

ANTI-SILICONE DROPS should not be seen as a replacement for a clean working area and thorough surface preparation. Always clean the surface to be painted with *MOTOSPRAY PREPWASH* before attempting to paint. Use clean cloth. Wipe *PREPWASH* on with one cloth and dry off with clean cloth before the *PREPWASH* dries on the surface. Replace the cloth regularly and do not reuse as this may spread contaminants.

Directions

Add 2 drops of *ANTI-SILICONE DROPS* to a standard 1 litre pot of ready mixed paint. Stir paint well and apply as usual.

Storage

Store in a cool dry place. Always replace the lid securely after use.

Safety

See material safety data sheet.

Standard Packages and Product Codes

30ml Dropper bottle SIL

The information contained in this bulletin is presented in good faith based on thorough laboratory and field testing but without warranty. As we have no control over the conditions under which these products are used, it is recommended that all products be tested by the end user to ensure the suitability of the product for the particular application and conditions.