



HiChem Industries Pty Ltd.
73 Hallam South Road Hallam, Vic 3803
Phone (03) 9796 3400 Fax (03) 9796 4500
ACN 006-542-767



PRODUCT INFORMATION SHEET

g:\secure\product information\woodprod\woodstop.doc 10-5-00

WOOD STOP PUTTY

Description

A heavy bodied, air drying, nitrocellulose based knifing putty for use with pre catalysed and nitrocellulose lacquers.

Uses

Ideal for filling nail holes, dents, scratches and other small surface imperfections prior to staining and painting.

Properties

- Easy to apply
- Ready for use
- Excellent adhesion
- Easy to sand
- Accepts Spirit Stains

Surface Preparation

Sand surface as required. Remove dust by blowing with air or wiping.

Application

WOOD STOP PUTTY is ready for use. Apply in thin coats as required. Where heavier builds are required use 2-3 applications, allowing 10 to 15 minutes drying time between coats. Problems may occur later if used for deep filling. Shrinking or cracking could occur if application is too heavy and built up without sufficient drying between coats.

Before final sanding allow a drying time of 30 minutes and up to 4 hours for heavier builds depending on the temperature. Sand with 180-240 grit paper.

Storage

Store in a cool dry place. Always replace the lid securely after use. If the *WOOD STOP PUTTY* thickens due to evaporation, it may be thinned with *REDUCER 285*.

Safety

See material safety data sheet

Standard Packages and Product Codes

600gram Product Code - WSP600

The information contained in this bulletin is presented in good faith based on thorough laboratory and field testing but without warranty. As we have no control over the conditions under which these products are used, it is recommended that all products be tested by the end user to ensure the suitability of the product for the particular application and conditions.