

HiChem Paint Technologies Pty.Ltd.

A.B.N. 95 064 139 653
 73 Hallam South Road, HALLAM, VICTORIA 3803.
 Telephone : {03} 9796 3400 Facsimile : {03} 9796 4500
 Email:msdsinfo@hichem.com.au www:hichem.com.au



IDENTIFICATION of the SUBSTANCE(S) and COMPOSITION

Product Name	1K SPOT REPAIR PRIMER - AEROSOL		Code	1KP400
Product Use	Use as a primer for small repairs on automotive surfaces.			
Ingredients	Name	CAS Number	Proportion w/w	
	Acetone	67 – 64 – 1	10 – <30 %	
	Di – Methyl Ether	115 – 10 – 6	30 – 60 %	
	Coloured Pigments/Extenders(Non-Hazardous)	Mixture	10 – <30 %	
	Polymeric Polyacrylated Resin (Non-Hazardous)	Not Known	10 – <30 %	
	Additives (Non-Hazardous)	Mixture	1 – <10 %	

HAZARD IDENTIFICATION

The product is classified both as Hazardous Substance and Dangerous Goods according to ASCC

Risk Phrases R

12	Extremely Flammable Gas
20/21/22	Harmful by inhalation, skin contact and if swallowed.
36/37/38	Irritating to the eyes, respiratory system and skin.
52/53/59	Harmful to aquatic systems and may cause long term adverse effects in the aquatic environment. Dangerous to ozone layer.
65/66/67	Harmful. May cause lung damage if swallowed. Repeated or prolonged exposure may cause skin dryness and cracking. Vapours may cause headaches, drowsiness and dizziness.

Safety Phrases S

2	Keep out of reach of children.
7/9	Keep containers tightly closed when not in use and also in a well ventilated area.
15	Keep away from heat.
16/33	Keep away from sources of ignition. Take precautionary measures against static electricity.
20/21	When using, do not eat, drink or smoke.
23.5	Do not breathe the vapours and spray mists
24/25	Avoid skin contact and with the eyes.
26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
27	Take off immediately all contaminated clothing.
28.1	In contact with the skin, wash immediately soap and plenty of water.
36/37/38/39	Wear protective clothing, including knee high boots, elbow length gloves, organic vapour – particulate respirator including eye and face protection.
45	In case of accident, or if you feel unwell, seek medical advice immediately. Show the label where possible.
57	Use appropriate containment to avoid environmental contamination.
62	If swallowed, do not induce vomiting: seek medical advice immediately. Show the label where possible.

ADG Classification AEROSOLS – with a capacity less than 1 Litre, UN 1950, Class 2.1, HAZCHEM 2Y.

SUSDP Classified as a Schedule S 5 poison.

FIRST AID MEASURES

<i>Inhalation</i>	If the applicator feels drowsy, dizzy, tired or experiencing headaches, remove the victim to the fresh air. Keep the victim warm and quiet until all symptoms subside.
<i>Ingestion</i>	Unlikely route of exposure. Give 2 glasses of water to drink. If any systems occur, clean DO NOT induce vomiting; seek URGENT medical attention if frothing from the mouth occurs.
<i>Eyes</i>	If splashed into eyes, hold eyes open, irrigate copiously with clean water for at least 15 minutes. Seek immediate medical attention if any irritation occurs.
<i>Skin</i>	If skin contact occurs, remove contaminated clothing, and wash thoroughly with soap and plenty of water. Seek medical attention if any irritation occurs.
<i>First Aid Facilities</i>	Clean Water Supply, soap or skin cleaner, barrier cream, emergency showers and eye wash stations.
<i>Advice to Doctor</i>	If poisoning occurs, consult with the Poisons Information Centre {Telephone 13 11 26 }. Have a copy of this material safety data sheet or label available.



FIRE FIGHTING MEASURES

<i>Extinguishing Media and Requirements</i>	Carbon Dioxide {CO ₂ }, alcohol resistant foam, dry chemical or water spray. DO NOT use water jets. Bund area with sand to prevent run – off entering waterways and drains.
<i>Fire Fighting Procedures & Precautions</i>	Fire – fighters should wear Chemical Splash Suit with attached Self – Contained Breathing Apparatus and gloves. Evacuate all non fire–fighting personnel away from the area. Turn off all electricity and power supplies. Keep containers cool with water spray or water to prevent rupture or burning. Move away all containers and equipment from the direction of the fire, if safe to do so. Keep upwind.
<i>Flammability Hazardous Decomposition Products</i>	Highly Flammable Gas. Flash Point =< – 25 °C On heating, containers may rupture and explode: contents may burn rapidly forming toxic gases including carbon monoxide. .



ACCIDENTAL RELEASE MEASURES

<i>Spills and Leaks</i>	Contain all spills and leaks. Avoid contamination with spilt material on surfaces. Remove all sources of ignition and NO SMOKING . Wear the recommended full body impervious clothing, gloves and breathing apparatus as per AS– NZ 1715/16. Keep upwind. Absorb all spilt contents onto sand or earth.
<i>Disposal</i>	Collect all residues into labelled and sealed containers for disposal via special waste collection services as per local Statutory Authority requirements.
<i>Other Precautions</i>	Avoid contaminating waterways, drains, water courses and sewage.



HANDLING and STORAGE

Handling	Keep out of reach of children. Avoid unnecessary contact with the material. After use before eating, drinking or smoking wash all exposed skin with soap and water.
Storage	Containers must be clearly labelled, rigid and strong. Store upright in a cool, dry, well ventilated area from heat, ignition sources and direct sunlight e.g. Flammable Goods Store as per AS 1940 requirements.

EXPOSURE CONTROLS

Exposure Standards TWA	Di Methyl Ether = No data available	Acetone = 1182 mg/m ³ .
Exposure Standards STEL	Di Methyl Ether = No data available	Acetone 2375 mg/m ³ .
Engineering Controls	During the application period, ensure there is adequate ventilation at all times e.g. preferably with doors and windows open. Do not used in a confined space	

PERSONAL PROTECTION

Inhalation AS –NZN 1715/16	The wearing of an Organic Vapour Respirator is recommended during the application period.
Eye AS –NZN 1337	The wearing of safety glasses fitted with side shields is recommended during the application period Do not wear contact lenses.
Gloves AS –NZN 2161	The wearing of Viton or PVC gloves is recommended during the application period.
Footwear AS –NZN 2210	The wearing of enclosed footwear is recommended during the application period.
Clothing AS –NZN 2919	The wearing of anti–static clothing made on natural or synthetic high temperature fibre is recommended during the spray application period.
Hearing AS –NZN 1270	Not required since the product is not applied by conventional spray
Other Requirements	Avoid contact with eyes and skin. Avoid inhaling spray mists and vapours.



PHYSICAL – CHEMICAL PROPERTIES

Appearance	A coloured liquid with a mild odour.
pH	Not required.
Vapour Pressure (Butyl Acetate = 1)	Greater than 1.0
Boiling Point °C	No data available
Density	0.87 (calculated value)
Solubility in water	Immiscible
Flash Point °C	< – 25 °C {literature value}
Flammability	No data available
Limits	
Auto Ignition °C	No data available
Volatile Components	Di Methyl Ether and Acetone.

STABILITY and REACTIVITY

Chemical Stability	Stable under normal conditions of use.
Conditions to avoid	Avoid contact with heat and all ignition sources.
Hazardous decomposition products	On heating, containers may rupture and explode: contents may burn rapidly forming toxic gases including carbon monoxide.
Incompatible materials	Incompatible with strong oxidizing agents
Hazardous Reactions	Will not polymerize.

TOXICOLOGICAL INFORMATION

Acute Toxicity Data

<i>Health Effects</i>	<i>Risk Phrase</i>	<i>Acetone</i>	<i>Di Methyl Ether</i>
Inhalation LC ₅₀ rat 4 hours	20	>20mg/L	> 20mg/L
Dermal LD ₅₀ rabbit	21	12100 mg/kg	> 2000 mg/kg
Oral LD ₅₀ rat	22	636 mg/kg	> 2000 mg/kg

Note

Risk phrases R20/21/22 has been assigned by the EEC Council Directive 67/548/EEC.
 Risk Phrases R20/21/22 – Harmful by inhalation, skin contact or if swallowed.

Acute Oral Toxicity (Dimethyl Ether and Acetone) rat	Low toxicity. Aspiration into lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.
Acute Dermal Toxicity (Dimethyl Ether and Acetone) rabbit	Low toxicity.
Acute Inhalation Toxicity (Dimethyl Ether and Acetone)rat	Low toxicity. High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea; continued inhalation may result in unconsciousness and/or death.

Health Effects

Inhalation	The inhalation of vapours and spray mist may cause acute irritation in the respiratory tract. Other symptoms may cause central nervous system depression resulting in headaches, dizziness, nausea, loss of co-ordination and impaired judgement.
Ingestion	May cause irritation
Eyes	Irritating to the eyes, including burning sensation, redness, swelling and/or blurred vision.
Skin	May cause degreasing effect on the skin resulting in contact dermatitis..
Carcinogenicity.	Not carcinogenic in animal studies
Mutagenicity	Not mutagenic in animal studies
	May cause foetotoxicity in animals. Does not impair fertility.

ECOLOGICAL INFORMATION

Environment	Harmful to aquatic environment (R52). May cause long – term adverse effects in the aquatic environment (R53). Danger to ozone layer (R 59).
--------------------	---

DISPOSAL CONSIDERATIONS

Collect all residues and placed into labelled and sealed containers. Do not incinerate or puncture empty containers after use. Crush all small empty containers. Dampen all unwanted cloths and rags in water prior to disposal. Do not recycle contents or spent containers. Ensure all contents do not pollute waterways, drains and other water courses.

TRANSPORT INFORMATION

UN number	1950		
Proper Shipping Name	AEROSOLS – with a capacity less than 1 Litre		
Class	2.1	Subsidiary Risk	Not Required
Packing Group	Not Assigned		
Emergency Procedures		Initial Emergency Response Guide	49
HAZCHEM	2Y		
IMDG			



REGULATORY INFORMATION

SUSDP Classified as a Schedule S 5 poison.

OTHER INFORMATION

Emergency Contact **Poisons Information Centre 13 11 26** **HiChem Paint Technologies (03) 9796 3400**

Disclaimer *Data provided is to best of HiChem Paint Technologies Proprietary Limited knowledge and believe to be accurate and reliable as of the date of issued. However no expressed or implied warranties are given. HiChem Paint Technologies Proprietary Limited cannot anticipate or control the conditions under which this information may be used. Therefore, it is user's responsibility to satisfy themselves as to the suitability and completeness of such information for their particular use. It is the responsibility of the user to ensure that the issue is current. This information given is a non-controlled document*