

HiChem Paint Technologies PTY. LTD.

A.B.N. 95 064 139 653

73 Hallam South Road, HALLAM, VICTORIA 3803.


Telephone : {03} 9796 3400 Facsimile : {03} 9796 4500

Email:msdsinfo@hichem.com.au www:hichem.com.au

**IDENTIFICATION of the SUBSTANCE(S) and COMPOSITION**

Product Name	BRUSH CLEANER	Code	BC500
Product Use	Use as a solvent cleaner for removal of paint from brushes..		
Ingredients	Name	CAS Number	Proportion w/w
	Mineral Turpentine	Not Known	60 –100 %
	Additives (Non – Hazardous)	Not Known	1 – 10 %

HAZARD IDENTIFICATION

Hazard Classification	Hazardous Substance, Dangerous Goods		
Chronic	Risk 65,66,67	Harmful. May cause lung damage if swallowed. Repeated exposure may cause skin dryness and cracking. Vapours may cause headaches, drowsiness and dizziness.	
Acute			
Skin	Risk 21,38	Harmful X _n , Irritant X _i	
Inhalation	Risk 20, 37	Harmful X _n , Irritant X _i	
Ingestion	Risk 22	Harmful X _n ,	
Eyes	Risk 36	Irritant X _i	
ADG Classification	FLAMMABLE LIQUID NOS, miscible in water, U.N.1993, Class 3, HAZCHEM 3[ , Packing Group III.		
SUSDP Classification	Classified as a Schedule S5 Poison.		

FIRST AID MEASURES

Inhalation	If the applicator feels drowsy, dizzy, tired or experiencing headaches, remove the victim to the fresh air. Keep the victim warm and quiet until all symptoms subside.
Ingestion	If swallowed and only if the person is conscious, give water to drink. DO NOT induce vomiting. Seek URGENT medical attention if frothing from the mouth occurs.
Eyes	If splashed into eyes, hold eyes open, irrigate copiously with clean water for at least 15 minutes. Seek immediate medical attention if any irritation occurs.
Skin	If skin contact occurs, remove contaminated clothing, and wash thoroughly with soap and plenty of water. Seek medical attention if any irritation occurs.
First Aid Facilities	Clean Water Supply, soap or skin cleaner, barrier cream, emergency showers and eye wash stations.
Advice to Doctor	If poisoning occurs, consult with the Poisons Information Centre {Telephone 13 11 26 }. Have a copy of this material safety data sheet or label available. Treat symptomatically.



FIRE FIGHTING MEASURES

***Extinguishing Media and Requirements
Fire Fighting Procedures & Precautions***

Carbon Dioxide {CO₂}, alcohol resistant foam, dry chemical or water spray. **DO NOT** use water jets. Bund area with sand to prevent run – off entering waterways and drains.

Fire – fighters should wear Chemical Splash Suit with attached Self – Contained Breathing Apparatus and gloves. Evacuate all non fire–fighting personnel away from the area. Turn off all electricity and power supplies. Keep containers cool with water spray or water to prevent rupture or burning. Move away all containers and equipment from the direction of the fire, if safe to do so. Keep upwind.



***Flammability
Hazardous
Decomposition
Products***

Flammable Liquid. Flash Point = 34 °C
On heating, containers may rupture and explode; contents may burn rapidly forming toxic gases including carbon monoxide.

ACCIDENTAL RELEASE MEASURES

Spills and Leaks

Contain all spills and leaks. Avoid contamination with spilt material on surfaces. Remove all sources of ignition and **NO SMOKING**. Wear the recommended full body impervious clothing, gloves and breathing apparatus as per AS– NZ 1715/16. Keep upwind. Absorb all spilt contents onto sand or earth.



Disposal

Collect all residues into labelled and sealed containers for disposal via special waste collection services as per local Statutory Authority requirements.

Other Precautions

Avoid contaminating waterways, drains, water courses and sewage.

HANDLING and STORAGE

Handling

Keep out of reach of children. Avoid unnecessary contact with the material. After use before eating, drinking or smoking wash all exposed skin with soap and water.

Storage

Containers must be clearly labelled, rigid and strong. Store upright in a cool, dry, well ventilated area from heat, ignition sources and direct sunlight e.g. Flammable Goods Store as per AS 1940 requirements.

EXPOSURE CONTROLS

***Exposure Standards MAK
Engineering Controls***

Mineral Turpentine = Not Known

When applying the product, ensure there is adequate ventilation during the application period.

PERSONAL PROTECTION

Inhalation

AS –NZS 1715/16

Eye

AS –NZS 1337

Gloves

AS –NZS 2161

Footwear

AS –NZS 2210

Clothing

AS –NZS 2919

Hearing

AS –NZS 1270

Other Requirements

It is advisable to wear an Organic Vapour Respirator is recommended during the application period.

It is advisable to wear safety glasses fitted with side shields recommended during the application period. Do not wear contact lenses.


It is advisable to wear Viton or PVC gloves recommended during the application period.

It is advisable to wear enclosed footwear is recommended during the application period

It is advisable to wear anti-static clothing made on natural or synthetic high temperature fibre is recommended during the application period

Not Required

Avoid contact with eyes and skin. Wear the recommended Personal Protective Equipment as described.



PHYSICAL – CHEMICAL PROPERTIES

Appearance

A colourless liquid with a mild odour.

pH

Not required.

Vapour Pressure

Greater than 1.

(Butyl Acetate = 1)

Boiling Point °C

150 – 175 °C {literature value}

Density

0.83 {literature value}

Solubility in water

Partially miscible

Flash Point °C

34 °C {literature value}

Flammability Limits

Lower Explosive Limit = 1.0 %

Upper Explosive Limit = 3.5 %

Auto Ignition °C

250 °C

Volatile Components

Organic Solvent

STABILITY and REACTIVITY

Chemical Stability

Stable under normal conditions of use.

Hazardous

Will not polymerize.

Polymerization

Conditions to avoid

Avoid contact heat and all ignition sources.

Incompatible materials

Incompatible with strong oxidizing agents

Hazardous decomposition products

Stable.

TOXICOLOGICAL INFORMATION

Inhalation

LC₅₀

rat Organic Solvent > 20mg/Litre for 4 hours

Skin

LD₅₀

rabbit Organic Solvent > 400 mg/kilogram bodyweight/day

Ingestion

LD₅₀

rat Organic Solvent > 200 mg/kilogram bodyweight/day

Eyes

Organic Solvents – irritant

Sensitization

No Data for Organic Solvents – non sensitizer

ECOLOGICAL INFORMATION

Environment No data available

DISPOSAL CONSIDERATIONS

Collect all residues and placed into labelled and sealed containers. Do not incinerate empty containers after use. Dampen all unwanted cloths and rags in water prior to disposal. Do not recycle contents or spent containers. Larger containers and drums may be sent to an approved drum recycler. Ensure all contents do not pollute waterways, drains and other water courses.

TRANSPORT INFORMATION

UN number 1993
Proper Shipping Name FLAMMABLE LIQUID NOS, immiscible in water.
Class 3 **Subsidiary Risk** Not Required
Packing Group III
Emergency Procedures EP 3303 **Initial Emergency Response Guide** 15
HAZCHEM 3[Y]
IMDG

**REGULATORY INFORMATION**

Risk Phrases R 65,66,67 Harmful. May cause lung damage if swallowed. Repeated exposure may cause skin dryness and cracking. Vapours may cause headaches, drowsiness and dizziness
Safety Phrases S 36/37/38 Irritating to eyes, respiratory system and skin.
 7/9 Keep containers closed and in a well ventilated area when not in use.
 23.2 Avoid breathing vapours.
 24/25 Avoid contact with skin and eyes.
 36/37/38/39 Wear recommended Personal Protective Equipment – protective clothing, gloves, boots, respirator and eye protection.
SUSDP Classification Classified as a Schedule S5 Poison.

OTHER INFORMATION

Emergency Contact **Poisons Information Centre 13 11 26 HiChem Industries (03) 9796 3400**

Disclaimer Data provided is to best of HiChem Industries Proprietary Limited knowledge and believe to be accurate and reliable as of the date of issued. However no expressed or implied warranties are given. HiChem Industries Proprietary Limited cannot anticipate or control the conditions under which this information may be used. Therefore, it is user's responsibility to satisfy themselves as to the suitability and completeness of such information for their particular use. It is the responsibility of the user to ensure that the issue is current. This information given is a non-controlled document