

HiChem Paint Technologies Pty.Ltd.

A.B.N. 95 064 139 653
73 Hallam South Road, HALLAM, VICTORIA 3803.
Telephone : {03} 9796 3400 Facsimile : {03} 9796 4500
Email:msdsinfo@hichem.com.au www:hichem.com.au



IDENTIFICATION of the SUBSTANCE(S) and COMPOSITION

Product Name	CONTACT ADHESIVE – AEROSOL	Code	CON 350
Product Use	An aerosol spray used for attaching automotive trims of to vehicles.		
Ingredients	Name	CAS Number	Proportion w/w
	Di Chloro Methane (Methylene Chloride)	75 – 09 – 2	10 – <30 %
	Toluene	108 – 88 – 3	1.0 – <10 %
	Naphtha (Petroleum) Hydrotreated Light	64742 – 49 – 0	10 – <30 %
	Liquefied Petroleum Gas	68476 – 85 – 7	30 – 60 %
	Polymeric Synthetic Resins (non – hazardous)	Mixture	1.0 – <10 %
	Additives (non – hazardous)	Mixture	0.1 – <1.0 %

HAZARD IDENTIFICATION

The product is classified as both **Dangerous Goods and Hazardous Substance** in accordance to ASCC

Risk Phrases R

- 12 Extremely Flammable Gas
21/22 Harmful in contact with the skin and if swallowed.
36/37/38 Irritating to the eyes, respiratory system and skin.
40 Limited evidence of a carcinogenic effect.
48/20 Harmful: Danger of serious damage to health by prolonged exposure through inhalation.
51/53/59 Toxic to aquatic organisms and may cause long term adverse effects in the aquatic environment. Dangerous for the ozone layer
63 Causes foetotoxicity in animals at doses which are maternally toxic.
65/66/67 Harmful. May cause lung damage if swallowed. Repeated or prolonged exposure may cause skin dryness and cracking. Vapours may cause headaches, drowsiness and dizziness.

Safety Phrases S

- 2 Keep out of reach of children.
7/9 Keep containers tightly closed when not in use and also in a well ventilated area.
15 Keep away from heat.
16/33 Keep away from sources of ignition. Take precautionary measures against static electricity.
20/21 When using, do not eat, drink or smoke.
23.5 Do not breathe vapours and spray mists.
24/25 Avoid skin contact and with the eyes.
26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
27 Take off immediately all contaminated clothing.
28.1 In contact with the skin, wash immediately soap and plenty of water.
36/37/38/39 The wearing of an Organic Vapour – Particulate Respirator, Safety Glasses fitted with side – shields, Viton or PVC gloves, enclosed footwear, high temperature and anti – static clothing.
45 In case of accident, or if you feel unwell, seek medical advice immediately. Show the label where possible.
62 If swallowed, do not induce vomiting: seek medical advice immediately. Show the label where possible.

ADG Classification AEROSOLS – with a capacity less than 1 Litre, UN 1950, HAZCHEM 3WE, Class 9, Initial Emergency Response Guide 49.

SUSDP Classified as a Schedule S 5 poison

FIRST AID MEASURES

<i>Inhalation</i>	If the applicator feels drowsy, dizzy, tired or experiencing headaches, remove the victim to the fresh air. Keep the victim warm and quiet until all symptoms subside.
<i>Ingestion</i>	Unlikely route of exposure. Give 2 glasses of clean water to drink. If any symptoms occur, DO NOT induce vomiting; seek URGENT medical attention if frothing from the mouth occurs.
<i>Eyes</i>	If sprayed into eyes, hold eyes open, irrigate copiously with clean water for at least 15 minutes. Seek immediate medical attention if any irritation occurs.
<i>Skin</i>	If skin contact occurs, remove contaminated clothing, and wash thoroughly with soap and plenty of water. Seek medical attention if any irritation occurs.
<i>First Aid Facilities</i>	Clean Water Supply, soap or skin cleaner, barrier cream, emergency showers and eye wash stations.
<i>Advice to Doctor</i>	If poisoning occurs, consult with the Poisons Information Centre {Telephone 13 11 26 }. Have a copy of this material safety data sheet or label available. Treat symptomatically as systems may be delayed for several hours after exposure.



FIRE FIGHTING MEASURES

<i>Extinguishing Media and Requirements</i>	Carbon Dioxide {CO ₂ }, alcohol resistant foam, dry chemical or water spray. DO NOT use water jets. Bund area with sand to prevent run – off entering waterways and drains.
<i>Fire Fighting Procedures & Precautions</i>	Fire – fighters must wear Chemical Splash Suit with attached Self – Contained Breathing Apparatus and gloves. Evacuate all non fire–fighting personnel away from the area. Turn off all electricity and power supplies. Keep containers cool with water spray or water to prevent rupture or burning. Move away all containers and equipment from the direction of the fire, if safe to do so. Keep upwind.
<i>Flammability Hazardous Decomposition Products</i>	Extremely Flammable Gas. Flash Point = < - 25 °C On heating, containers may rupture and explode: contents may burn rapidly forming toxic gases including carbon monoxide, chlorine and phosgene.



ACCIDENTAL RELEASE MEASURES

<i>Spills and Leaks</i>	Contain all spills and leaks. Avoid contamination with spilt material on surfaces. Remove all sources of ignition and NO SMOKING . Wear the recommended full body impervious clothing, gloves and breathing apparatus as per AS– NZ 1715/16. Keep upwind. Absorb all spilt contents onto sand or earth.
<i>Disposal</i>	Collect all residues into labelled and sealed containers for disposal via special waste collection services as per local Statutory Authority requirements.
<i>Other Precautions</i>	Avoid contaminating waterways, drains, water courses and sewage.



HANDLING and STORAGE


Handling	Keep out of reach of children. Avoid unnecessary contact with the material. After use before eating, drinking or smoking wash all exposed skin with soap and water.
Storage	Containers must be clearly labelled, rigid and strong. Store upright in a cool, dry, well ventilated area from heat, ignition sources and direct sunlight e.g. Flammable Goods Store as per AS 1940 requirements.

EXPOSURE CONTROLS

Exposure Standards MAK Exposure Standards STEL Engineering Controls	<p>Liquefied Petroleum Gas = 1800 mg/m³ Di Chloro Methane = 350 mg/m³. Naphtha (Petroleum) Hydrotreated Light = 100 mg/m³. Toluene = 190 mg/ m³. Toluene = 575 mg/ m³.</p> <p>The use of local exhaust ventilation equipment is required. All ventilation equipment must be fitted with flame and explosion proof electrical fittings. Do not use in a confined space.</p>
--	---

PERSONAL PROTECTION

Inhalation AS -NZS 1715/16	The wearing of an Organic Vapour Respirator must be worn at all times during the application period.
Eye AS -NZS 1337	The wearing of safety glasses fitted with side shields must be worn during the application period. Do not wear contact lenses.
Gloves AS -NZS 2161	The wearing of Viton or PVC gloves must be worn during the application period.
Footwear AS -NZS 2210	The wearing of enclosed footwear must be worn during the application period.
Clothing AS -NZS 2919	The wearing of anti-static clothing made on natural or synthetic high temperature fibre must be worn during the application period.
Hearing AS -NZS 1270	Not required.
Other Requirements	Avoid contact with eyes and skin. Avoid inhaling vapours and spray mists at all times.



PHYSICAL – CHEMICAL PROPERTIES

Appearance	A coloured gas with a mild odour.	
pH	Not required.	
Vapour Pressure (Butyl Acetate = 1)	Greater than 1.0	
Boiling Point °C	Not Known	
Density	0.82 {calculated value}	
Solubility in water	Immiscible	
Flash Point °C	< - 25 °C {literature value}	
Flammability Limits	Lower Explosive Limit = 1.0 %	Upper Explosive Limit = 22.0 %
Auto Ignition °C	250 °C {literature value}	
Volatile Components	Organic Solvents.	

STABILITY and REACTIVITY

Chemical Stability	Stable under normal conditions of use.
Conditions to avoid	Avoid contact with heat and all ignition sources.
Hazardous decomposition products	On heating, containers will rupture and explode: contents may burn rapidly forming toxic gases including carbon monoxide.
Incompatible materials	Incompatible with strong oxidizing agents
Hazardous Reactions	Will not polymerize.

TOXICOLOGICAL INFORMATION

<i>Health Effects</i>	<i>Risk Phrase</i>	<i>Naphtha (Petroleum) Hydrotreated Light</i>	<i>Di Chloro Methane</i>	<i>Toluene</i>	<i>Liquefied Petroleum Gas</i>
Inhalation LC ₅₀ rat	20	>20 mgm/L	>20 mgm/L	>20 mgm/L	>20 mgm/L
Dermal LD ₅₀ rabbit	21	>2000 mgm/kgm	>2000 mgm/kgm	>2000 mgm/kgm	>2000 mgm/kgm
Oral LD ₅₀ rat	22	>2000 mgm/kgm	>2000 mgm/kgm	640 mgm/kgm	>2000 mgm/kgm

Note

Risk phrases R21/22, 48/20 has been assigned by the EEC Council Directive 67/548/EEC.

Risk Phrases R21/22, 48/20 – Harmful with skin contact or if swallowed; Harmful, danger of serious damage to health prolonged exposure through inhalation.

Acute Oral Toxicity rat Moderate toxicity. Aspiration into lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

Acute Dermal Toxicity rabbit Low toxicity

Acute Inhalation Toxicity rat Low toxicity. High concentrations may cause central nervous system depression resulting in headaches, dizziness, nausea, loss of co-ordination and impaired judgement: continued inhalation may result in unconsciousness and/or death.

OTHER TOXICOLOGICAL INFORMATION (CONTINUED)

Health Effects

Inhalation	Other symptoms may cause dizziness, nausea, coughing, lack of co – ordination and impair judgement.
Ingestion	Large quantities may cause nausea and vomiting.
Eyes	Irritating to the eyes, including burning sensation, redness, swelling and/or blurred vision.
Skin	Will have degreasing effect on the skin may result in contact dermatitis.
Carcinogenicity	Limited evidence of a carcinogenic effect.
Mutagenicity	Not mutagenic in animal studies
Reproductive Toxicity	Causes foetotoxicity in animals at doses which are maternally toxic. Does not impair fertility.

ECOLOGICAL INFORMATION

Environment	Toxic to aquatic organisms (R51). May cause long – term adverse effects in the aquatic environment (R53). Dangerous for the ozone layer (R59)
--------------------	---


DISPOSAL CONSIDERATIONS

Collect all residues and placed into labelled and sealed containers. Do not incinerate empty containers after use. Dampen all unwanted cloths and rags in water prior to disposal. Do not recycle contents or spent containers. Crush all small empty containers. Larger containers and drums may be sent to an approved drum recycler. Ensure all contents do not pollute waterways, drains and other water courses.



TRANSPORT INFORMATION

UN number	1950		
Proper Shipping Name	AEROSOLS, capacity less than 1 Litre		
Class	9	Subsidiary Risk	Not Required
Packing Group	Not Assigned		
Emergency Procedures	3900	Initial Emergency Response Guide	49
HAZCHEM	3WE		
IMDG	Not Known		



REGULATORY INFORMATION

SUSDP Classified as a Schedule S 5 poison.

OTHER INFORMATION

Emergency Contact	Poisons Information Centre 13 11 26	HiChem Paint Technologies
Disclaimer		(03) 9796 3400

Data provided is to best of HiChem Paint Technologies Proprietary Limited knowledge and believe to be accurate and reliable as of the date of issued. However no expressed or implied warranties are given. HiChem Paint Technologies Proprietary Limited cannot anticipate or control the conditions under which this information may be used. Therefore, it is user's responsibility to satisfy themselves as to the suitability and completeness of such information for their particular use. It is the responsibility of the user to ensure that the issue is current. This information given is a non-controlled document