

HiChem Paint Technologies Pty.Ltd.

A.B.N. 95 064 139 653

73 Hallam South Road, HALLAM, VICTORIA 3803.

Telephone : {03} 9796 3400 Facsimile : {03} 9796 4500

Email: msdsinfo@hichem.com.au www.hichem.com.au**IDENTIFICATION of the SUBSTANCE(S) and COMPOSITION**

Product Name	CONCRETE CLEANER	Code	
Product Use	A solvent based, water miscible cleaning solvent applied by brush for the cleaning of concrete prior to painting or for removal of oil or grease from concrete surfaces.		
Ingredients	Name	CAS Number	Proportion w/w
	Solvent Naphtha (Petroleum) Light Aliphatic	64742 – 88 – 7	30 – 60 %
	Solvent Naphtha (Petroleum) Light Aromatic	64742 – 95 – 6	30 – 60 %
	Additives (Non – Hazardous)	Mixture	1.0 – 10 %
	Ethyl Benzene	100 – 41 – 4	1.0 – 10 %

HAZARD IDENTIFICATION

The product is classified as both **Dangerous Goods and Hazardous Substance** in accordance to ASCC

Risk Phrases R

- 10 Flammable Liquid
 20/21/22 Harmful in contact with the skin and if swallowed.
 36/37/38 Irritating to the eyes, respiratory system and skin.
 40 Limited evidence of a carcinogenic effect
 51/53 Toxic to aquatic organisms and may cause long term adverse effects in the aquatic environment.
 63 Causes foetotoxicity in animals at doses which are maternally toxic.
 65/66/67 Harmful. May cause lung damage if swallowed. Repeated or prolonged exposure may cause skin dryness and cracking. Vapours may cause headaches, drowsiness and dizziness.

Safety Phrases S

- 2 Keep out of reach of children.
 7/9 Keep containers tightly closed when not in use and also in a well ventilated area.
 15 Keep away from heat.
 16/33 Keep away from sources of ignition. Take precautionary measures against static electricity.
 20/21 When using, do not eat, drink or smoke.
 23.2 Do not breathe vapours.
 24/25 Avoid skin contact and with the eyes.
 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
 27 Take off immediately all contaminated clothing.
 28.1 In contact with the skin, wash immediately soap and plenty of water.
 36/37/38/39 The wearing of an Organic Vapour Respirator, Safety Glasses fitted with side – shields, Viton or PVC gloves, hearing protection, hair protection, enclosed footwear, high temperature and anti – static clothing.
 45 In case of accident, or if you feel unwell, seek medical advice immediately. Show the label where possible.
 62 If swallowed, do not induce vomiting: seek medical advice immediately. Show the label where possible.

ADG Classification FLAMMABLE LIQUID, N.O.S., miscible in water, UN 1993, HAZCHEM 2 S, Class 3, Packing Group III, Initial Emergency Response Guide 15

SUSDP Classified as a Schedule S 5 poison

FIRST AID MEASURES

Inhalation	If the applicator feels drowsy, dizzy, tired or experiencing headaches, remove the victim to the fresh air. Keep the victim warm and quiet until all symptoms subside.
Ingestion	If swallowed, and only if the person is conscious, give plenty of water to drink. Do NOT induce vomiting. Seek medical attention if any symptoms occur.
Eyes	If splashed into eyes, hold eyes open, irrigate copiously with clean water for at least 15 minutes. Seek immediate medical attention if any irritation occurs.
Skin and Hair	If skin or hair contact occurs, remove all contaminated clothing, flush skin and hair with running water. Seek medical attention if any irritation occurs.
First Aid Facilities	Clean Water Supply, soap or skin cleaner, barrier cream, emergency showers and eye wash stations.
Advice to Doctor	If poisoning occurs, consult with the Poisons Information Centre {Telephone 13 11 26 }. Have a copy of this material safety data sheet or label available. Treat symptomatically as systems may be delayed for several hours after exposure.

**FIRE FIGHTING MEASURES**

Extinguishing Media and Requirements	Carbon Dioxide {CO ₂ }, alcohol resistant foam, dry chemical or water spray. DO NOT use water jets. Bund area with sand to prevent run – off entering waterways and drains.
Fire Fighting Procedures & Precautions	Fire – fighters must wear Chemical Splash Suit with attached Self – Contained Breathing Apparatus and gloves. Evacuate all non fire–fighting personnel away from the area. Turn off all electricity and power supplies. Keep containers cool with water spray or water to prevent rupture or burning. Move away all containers and equipment from the direction of the fire, if safe to do so. Keep upwind.
Flammability Hazardous Decomposition Products	Flammable Liquid. Flash Point = 34 °C On heating, containers may rupture and explode: contents may burn rapidly forming toxic gases including carbon monoxide.

**ACCIDENTAL RELEASE MEASURES**

Spills and Leaks	Remove all sources of ignition and NO SMOKING . Wear the recommended full body impervious clothing, gloves and breathing apparatus as per AS– NZ 1715/16. Keep upwind. Remove all unwanted personnel away from the contaminated area.
Disposal	Concrete Cleaner is water miscible. Dilute the spilt contents with water and absorb onto dry sand or soil for disposal by an approved method. Contact the local Statutory Authorities.
Other Precautions	Avoid contaminating waterways, drains, water courses and sewage.



HANDLING and STORAGE


Handling	Keep out of reach of children. Avoid unnecessary contact with the material. After use before eating, drinking or smoking wash all exposed skin and hair with soap and water.
Storage	Containers must be clearly labelled, rigid and strong. Store upright in a cool, dry, well ventilated area from heat, ignition sources and direct sunlight e.g. Flammable Goods Store as per AS 1940 requirements.

EXPOSURE CONTROLS

Exposure Standards MAK	Solvent Naphtha (Petroleum) Light Aromatic = 480 mg/m ³ . (as Mineral Turpentine) Solvent Naphtha (Petroleum) Light Aliphatic = 480 mg/m ³ . (as Mineral Turpentine) Ethyl Benzene = 440 mg/m ³ .
Exposure Standards STEL	No data available
Engineering Controls	Not required since the product is used on exterior surfaces.

PERSONAL PROTECTION

Inhalation AS –NZS 1715/16	The wearing of an Organic Vapour Respirator should be worn at all times during handling and application period.
Eye AS –NZS 1337	The wearing of safety glasses fitted with side shields should be worn during handling and application period. Do not wear contact lenses.
Gloves AS –NZS 2161	The wearing of Viton or PVC gloves should be worn during handling and application period.
Footwear AS –NZS 2210	The wearing of enclosed footwear should be worn during handling and application period.
Clothing AS –NZS 2919	The wearing of anti-static clothing made on natural or synthetic high temperature fibre should be worn during handling and application period.
Hearing AS –NZS 1270	Not required.
Other Requirements	Avoid contact with eyes, skin and hair. The wearing of recommended Personal Protective Equipment as described including hair protection during handling and application period.

**PHYSICAL – CHEMICAL PROPERTIES**

Appearance	A colourless liquid with a mild odour.	
pH	Not Known.	
Vapour Pressure (Butyl Acetate = 1)	Less than 1.0	
Boiling Point °C	150 – 200 °C {literature value}	
Density	0.84 {calculated value}	
Solubility in water	Immiscible	
Flash Point °C	34 °C {literature value}	
Flammability Limits	Lower Explosive Limit = 1.0 %	Upper Explosive Limit = 7.8 %
Auto Ignition °C	250 °C {literature value}	
Volatile	Organic Solvents.	

*Components***STABILITY and REACTIVITY**

Chemical Stability	Stable under normal conditions of use.
Conditions to avoid	Avoid contact with heat and all ignition sources.
Hazardous decomposition products	On heating, containers may rupture and explode: contents may burn rapidly forming toxic gases including carbon monoxide.
Incompatible materials	Incompatible with strong oxidizing agents
Hazardous Reactions	Will not polymerize.

TOXICOLOGICAL INFORMATION

<i>Health Effects</i>	<i>Risk Phrase</i>	Solvent Naphtha (Petroleum) Light Aromatic/Aliphatic (as Mineral Turpentine)	<i>Ethyl Benzene</i>
Inhalation LC₅₀ rat	20	>20 mgm/L	>20 mgm/L
Dermal LD₅₀ rabbit	21	>2000 mgm/kg	>2000 mgm/kg
Oral LD₅₀ rat	22	>2000 mgm/kg	>2000 mgm/kg

Note

Risk phrases R20/21/22 has been assigned by the EEC Council Directive 67/548/EEC.
Risk Phrases R20/21/22 – Harmful by inhalation, skin contact or if swallowed.

Acute Oral Toxicity rat	Low toxicity. Aspiration into lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.
Acute Dermal Toxicity rabbit	Low toxicity
Acute Inhalation Toxicity rat	Low toxicity. High concentrations may cause central nervous system depression resulting in headaches, dizziness, nausea, loss of co-ordination and impaired judgement: continued inhalation may result in unconsciousness and/or death.

OTHER TOXICOLOGICAL INFORMATION**Other Health Effects**

Inhalation	Vapours may cause dizziness and drowsiness.
Ingestion	May cause lung damage if swallowed.
Eyes	Irritating to the eyes, including burning sensation, redness, swelling and/or blurred vision.
Skin	Irritating on the skin may result in contact dermatitis. Repeated or prolonged exposure may cause skin dryness or cracking.
Carcinogenicity	Limited evidence of a carcinogenic effect.
Mutagenicity	Not mutagenic in animal studies
Reproductive Toxicity	Causes foetotoxicity in animals at doses which are maternally toxic. Does not impair fertility.

ECOLOGICAL INFORMATION

Environment	Toxic to aquatic organisms (R51). May cause long – term adverse effects in the aquatic environment (R53).
--------------------	--

DISPOSAL CONSIDERATIONS

Collect all residues and placed into labelled and sealed containers. Do not incinerate empty containers after use. Dampen all unwanted cloths and rags in water prior to disposal. Do not recycle contents or spent containers. Crush all small empty containers. Larger containers and drums may be sent to an approved drum recycler. Ensure all contents do not pollute waterways, drains and other water courses.

**TRANSPORT INFORMATION**

UN number	1993		
Proper Shipping Name	FLAMMABLE LIQUID, N.O.S. miscible in water		
Class	3	Subsidiary Risk	Not Required
Packing Group	III		
Emergency Procedures	3305	Initial Emergency Response Guide	15
HAZCHEM	3[Y]E		
IMDG	Not Known		

**REGULATORY INFORMATION**

SUSDP Classified as a Schedule S 5 poison.

OTHER INFORMATION

Emergency Contact	Poisons Information Centre 13 11 26	HiChem Paint Technologies (03) 9796 3400
Disclaimer	<i>Data provided is to best of HiChem Paint Technologies Proprietary Limited knowledge and believe to be accurate and reliable as of the date of issued. However no expressed or implied warranties are given. HiChem Paint Technologies Proprietary Limited cannot anticipate or control the conditions under which this information may be used. Therefore, it is user's responsibility to satisfy themselves as to the suitability and completeness of such information for their particular use. It is the responsibility of the user to ensure that the issue is current. This information given is a non-controlled document</i>	