

HiChem Paint Technologies Pty Ltd

A.B.N. 95 064 139 653

73 Hallam South Road, HALLAM, VICTORIA 3803.

Telephone : {03} 9796 3400

Facsimile : {03} 9796 4500

Email: msdsinfo@hichem.com.auWebsite: www.hichem.com.au**IDENTIFICATION of the SUBSTANCE(S) and COMPOSITION**

Product Name	2 PACK CVI FINISH – LEAD CONTAINING COLOURS	Code	CVI
Product Use	2 Pack Colour Finish for painting of commercial vehicles and industrial use.		
Ingredients	Name	CAS Number	Proportion w/w
	Lead Chromate {as Lead}	7758 – 97 – 6	10 – 30 %
	Lead Chromate {as Chromium}	7758 – 97 – 6	1 – 10 %
	Xylene	1330– 20 – 7	10 – 30 %
	Propylene Glycol Mono Methyl Ether Acetate	108 – 65 – 6	10 – 30 %
	Synthetic Resins (Non-Hazardous)	Not Known	10 – 30 %
	Additives (Non-Hazardous)	Not Known	1 – 10 %

HAZARD IDENTIFICATION**Hazardous Substance**

Chronic Risk 33,40,
65,66,67

Dangerous Goods

Danger of cumulative effects. Limited evidence of a carcinogenic effect.
Harmful. May cause lung damage if swallowed. Repeated exposure may cause skin dryness and cracking. Vapours may cause headaches, drowsiness and dizziness.

Acute

Skin Risk 21,38
Inhalation Risk 20,37
Ingestion Risk 22
Eyes Risk 36

Harmful X_n, Irritant X_i
Harmful X_n Irritant X_i
Harmful X_n
Irritant X_i

Safety Phrases

7/9,23.5,24/25,36/37/39

Further description, refer to page 4.

ADG

PAINT– immiscible in water, UN 1263, Class 3, Packing Group III,

Classification

HAZCHEM 3[Y].

SUSDP

Classified as a Schedule S 6 poison.

Classification**FIRST AID MEASURES****Inhalation**

If the applicator feels drowsy, dizzy, tired or experiencing headaches, remove the victim to the fresh air. Keep the victim warm and quiet until all symptoms subside.

Ingestion

If swallowed and only if the person is conscious, give water to drink. **DO NOT** induce vomiting. Seek URGENT medical attention if frothing from the mouth occurs.

Eyes

If splashed into eyes, hold eyes open, irrigate copiously with clean water for at least 15 minutes. Seek immediate medical attention if any irritation occurs.

Skin

If skin contact occurs, remove contaminated clothing, and wash thoroughly with soap and plenty of water. Seek medical attention if any irritation occurs.

First Aid

Clean Water Supply, soap or skin cleaner, barrier cream, emergency showers and eye wash stations.

Facilities**Advice to Doctor**

If poisoning occurs, consult with the Poisons Information Centre {Telephone **13 11 26**}. Have a copy of this material safety data sheet or label available. Treat symptomatically.



FIRE FIGHTING MEASURES

Extinguishing Media and Requirements Fire Fighting Procedures & Precautions

Carbon Dioxide {CO₂}, alcohol resistant foam, dry chemical or water spray. **DO NOT** use water jets. Bund area with sand to prevent run – off entering waterways and drains. Fire – fighters should wear Chemical Splash Suit with attached Self – Contained Breathing Apparatus and gloves. Evacuate all non fire–fighting personnel away from the area. Turn off all electricity and power supplies. Keep containers cool with water spray or water to prevent rupture or burning. Move away all containers and equipment from the direction of the fire, if safe to do so. Keep upwind.



Flammability Hazardous Decomposition Products

Flammable Liquid. Flash Point = 27 °C
On heating, containers may rupture and explode: contents may burn rapidly forming toxic gases including carbon monoxide and oxides of nitrogen.

ACCIDENTAL RELEASE MEASURES

Spills and Leaks

Contain all spills and leaks. Avoid contamination with spilt material on surfaces. Remove all sources of ignition and **NO SMOKING**. Wear the recommended full body impervious clothing, gloves and breathing apparatus as per AS– NZ 1715/16. Keep upwind. Absorb all spilt contents onto sand or earth.



Disposal

Collect all residues into labelled and sealed containers for disposal via special waste collection services as per local Statutory Authority requirements.

Other Precautions

Avoid contaminating waterways, drains, water courses and sewage.

HANDLING and STORAGE

Handling

Keep out of reach of children. Avoid unnecessary contact with the material. After use before eating, drinking or smoking wash all exposed skin with soap and water.

Storage

Containers must be clearly labelled, rigid and strong. Store upright in a cool, dry, well ventilated area from heat, ignition sources and direct sunlight e.g. Flammable Goods Store as per AS 1940 requirements.


EXPOSURE CONTROLS

Exposure Standards MAK Engineering Controls

Propylene Glycol Mono Methyl Ether Acetate = 270 mg/m³.
Lead = 0.15 mg/m³. Chromium = 0.05 mg/m³. Xylene = 350 mg/m³.
When mixing and spraying of both CVI and its corresponding Isocyanate Hardener, all work must be performed out in approved spray booth in accordance with Australian Standards.

PERSONAL PROTECTION

Inhalation <i>AS –NZN 1715/16</i>	The wearing of Positive Pressure Air Supplied Full Face Respirator must be worn at all times during the mixing and spray application period; until all spray mists are efficiently dispersed from the spray booth atmosphere before exiting.
Eye <i>AS –NZN 1337</i>	The wearing of safety glasses fitted with side shields should be worn at all times during the mixing and spray application period. Do not wear contact lenses.
Gloves <i>AS –NZN 2161</i>	The wearing of Viton or PVC gloves should be worn at all times during the mixing and spray application period.
Footwear <i>AS –NZN 2210</i>	The wearing of enclosed footwear should be worn at all times during the mixing and spray application period
Clothing <i>AS –NZN 2919</i>	The wearing of anti–static clothing made on natural or synthetic high temperature fibre should be worn at all times during the mixing and spray application period
Hearing <i>AS –NZN 1270</i>	The wearing of hearing protection when applying by conventional spray is recommended during the spraying application period
Other Requirements	Avoid contact with eyes and skin. Avoid inhaling spray mists and vapours.



PHYSICAL – CHEMICAL PROPERTIES

Appearance	A coloured liquid with a strong odour.	
pH	Not required.	
Vapour Pressure <i>(Butyl Acetate = 1)</i>	Greater than 1.	
Boiling Point °C	145 – 165 °C {literature value}	
Density	1.3 {calculated value}	
Solubility in water	Immiscible	
Flash Point °C	27 °C {literature value}	
Flammability Limits	Lower Explosive Limit = 1.0 %	Upper Explosive Limit = 10.8%
Auto Ignition °C	315 °C {literature value}	
Volatile Components	Organic Solvents	

STABILITY and REACTIVITY

Chemical Stability	Stable under normal conditions of use.
Hazardous decomposition products	On heating, containers may rupture and explode: contents may burn rapidly forming toxic gases including carbon monoxide and oxides of nitrogen.
Conditions to avoid	Avoid contact with heat and all ignition sources.
Incompatible materials	Incompatible with strong oxidizing agents
Hazardous Reactions	Will not polymerize.

TOXICOLOGICAL INFORMATION

Inhalation	LC ₅₀	rat	Organic Solvents > 20mg/Litre for 4 hours
Skin	LD ₅₀	rabbit	Organic Solvents > 400 mg/kilogram bodyweight/day
Ingestion	LD ₅₀	rat	Organic Solvents and Lead Chromate > 200 mg/kilogram bodyweight/day
Eyes & Skin			Organic Solvents – irritant
Sensitization			The mixed product may cause asthma – type symptoms after being sensitized.
Health Effects			Not recommended for applicators that have respiratory ailments.

ECOLOGICAL INFORMATION

Environment R53. May cause long – term adverse effects to the aquatic environment

DISPOSAL CONSIDERATIONS

Collect all residues and placed into labelled and sealed containers. Do not incinerate empty containers after use. Dampen all unwanted cloths and rags in water prior to disposal. Do not recycle contents or spent containers. Crush all small empty containers. Larger containers and drums may be sent to an approved drum recycler. Ensure all contents do not pollute waterways, drains and other water courses.

TRANSPORT INFORMATION

UN number	1263		
Proper Shipping Name	PAINT, immiscible in water		
Class	3	Subsidiary Risk	Not Required
Packing Group	III		
Emergency Procedures	EP 3303	Initial Emergency Response Guide	15
HAZCHEM	3[<input checked="" type="checkbox"/>]		
IMDG			

**REGULATORY INFORMATION**

Risk Phrases R	33,40, 65,66,67	Danger of cumulative effects. Limited evidence of a carcinogenic effect. Harmful. May cause lung damage if swallowed. Repeated exposure may cause skin dryness and cracking. Vapours may cause headaches, drowsiness and dizziness
	20/21/22	Harmful by inhalation, skin contact and if swallowed.
	36/37/38	Irritating to eyes, respiratory tract and skin.
	10	Flammable
Safety Phrases S	7/9	Keep containers closed and in a well ventilated area when not in use.
	23.5	Avoid breathing vapours or spray mist.
	24/25	Avoid contact with skin and eyes.
	36/37/39	Wear recommended Personal Protective Equipment – protective clothing, gloves, boots, respirator, eyes and hearing protection.
SUSDP Classification	Classified as a Schedule S 6 Poison. Contains maximum 35% Lead and 9% Chromium of the Non – Volatile Content of the paint.	

OTHER INFORMATION

Emergency Contact **Poisons Information Centre 13 11 26** **HiChem Paint Technologies (03)**
9796 3400

Disclaimer *Data provided is to best of HiChem Paint Technologies Proprietary Limited knowledge and believe to be accurate and reliable as of the date of issued. However no expressed or implied warranties are given. HiChem Paint Technologies Proprietary Limited cannot anticipate or control the conditions under which this information may be used. Therefore, it is user's responsibility to satisfy themselves as to the suitability and completeness of such information for their particular use. It is the responsibility of the user to ensure that the issue is current. This information given is a non-controlled document*

Version 1 - New