

HiChem Paint Technologies Pty.Ltd.

A.B.N. 95 064 139 653

73 Hallam South Road, HALLAM, VICTORIA 3803.

Telephone : {03} 9796 3400

Facsimile : {03} 9796 4500

Email: markw@hichem.com.au

www:hichem.com.au



IDENTIFICATION of the SUBSTANCE(S) and COMPOSITION

Product Name	FADE OUT REDUCER 410 – AEROSOL	Code	FOR 400
Product Use	Use as an aerosol blending reducer for 410 Basecoats on automotive basecoats		
Ingredients	Name	CAS Number	Proportion w/w
	Cyclohexanone	108 – 94 – 1	10 – <30 %
	Propylene Glycol Mono Methyl Ether Acetate	108 – 65 – 6	10 – <30 %
	Liquefied Petroleum Gas	68746 – 85 – 7	30 – 60 %

HAZARD IDENTIFICATION

The product is classified both as **Hazardous Substance** and **Dangerous Goods** in accordance to ASCC

Risk Phrases R

- 12 Extremely Flammable Gas
- 20/21/22 Harmful by inhalation, skin contact and if swallowed.
- 36/38 Irritating to the eyes and skin.
- 52/53/59 Harmful to aquatic systems and may cause long term adverse effects in the aquatic environment. Dangerous to ozone layer.
- 65/66/67 Harmful. May cause lung damage if swallowed. Repeated or prolonged exposure may cause skin dryness and cracking. Vapours may cause headaches, drowsiness and dizziness.

Safety Phrases S

- 2 Keep out of reach of children.
- 7/9 Keep containers tightly closed when not in use and also in a well ventilated area.
- 15 Keep away from heat.
- 16/33 Keep away from sources of ignition. Take precautionary measures against static electricity.
- 20/21 When using, do not eat, drink or smoke.
- 23.5 Do not breathe the vapours and spray mists
- 24/25 Avoid skin contact and with the eyes.
- 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- 27 Take off immediately all contaminated clothing.
- 28.1 In contact with the skin, wash immediately soap and plenty of water.
- 36/37/38/39 Wear protective clothing, including knee high boots, elbow length gloves, organic vapour – particulate respirator including eye and face protection.
- 45 In case of accident, or if you feel unwell, seek medical advice immediately. Show the label where possible.
- 57 Use appropriate containment to avoid environmental contamination.
- 62 If swallowed, do not induce vomiting: seek medical advice immediately. Show the label where possible.

ADG Classification AEROSOLS – with a capacity less than 1 Litre, UN 1950, Class 2.1, HAZCHEM 2Y.

SUSDP Classified as a Schedule S 5 poison.

FIRST AID MEASURES

<i>Inhalation</i>	If the applicator feels drowsy, dizzy, tired or experiencing headaches, remove the victim to the fresh air. Keep the victim warm and quiet until all symptoms subside.
<i>Ingestion</i>	Unlikely route of exposure. Give 2 glasses of water to drink. If any systems occur, clean DO NOT induce vomiting; seek URGENT medical attention if frothing from the mouth occurs.
<i>Eyes</i>	If splashed into eyes, hold eyes open, irrigate copiously with clean water for at least 15 minutes. Seek immediate medical attention if any irritation occurs.
<i>Skin</i>	If skin contact occurs, remove contaminated clothing, and wash thoroughly with soap and plenty of water. Seek medical attention if any irritation occurs.
<i>First Aid Facilities</i>	Clean Water Supply, soap or skin cleaner, barrier cream, emergency showers and eye wash stations.
<i>Advice to Doctor</i>	If poisoning occurs, consult with the Poisons Information Centre {Telephone 13 11 26 }. Have a copy of this material safety data sheet or label available.



FIRE FIGHTING MEASURES

<i>Extinguishing Media and Requirements</i>	Carbon Dioxide {CO ₂ }, alcohol resistant foam, dry chemical or water spray. DO NOT use water jets. Bund area with sand to prevent run – off entering waterways and drains.
<i>Fire Fighting Procedures & Precautions</i>	Fire – fighters should wear Chemical Splash Suit with attached Self – Contained Breathing Apparatus and gloves. Evacuate all non fire–fighting personnel away from the area. Turn off all electricity and power supplies. Keep containers cool with water spray or water to prevent rupture or burning. Move away all containers and equipment from the direction of the fire, if safe to do so. Keep upwind.
<i>Flammability Hazardous Decomposition Products</i>	Highly Flammable Gas. Flash Point =< – 25 °C On heating, containers may rupture and explode: contents may burn rapidly forming toxic gases including carbon monoxide. .



ACCIDENTAL RELEASE MEASURES

<i>Spills and Leaks</i>	Contain all spills and leaks. Avoid contamination with spilt material on surfaces. Remove all sources of ignition and NO SMOKING . Wear the recommended full body impervious clothing, gloves and breathing apparatus as per AS– NZ 1715/16. Keep upwind. Absorb all spilt contents onto sand or earth.
<i>Disposal</i>	Collect all residues into labelled and sealed containers for disposal via special waste collection services as per local Statutory Authority requirements.
<i>Other Precautions</i>	Avoid contaminating waterways, drains, water courses and sewage.



HANDLING and STORAGE


Handling	Keep out of reach of children. Avoid unnecessary contact with the material. After use before eating, drinking or smoking wash all exposed skin with soap and water.
Storage	Containers must be clearly labelled, rigid and strong. Store upright in a cool, dry, well ventilated area from heat, ignition sources and direct sunlight e.g. Flammable Goods Store as per AS 1940 requirements.

EXPOSURE CONTROLS

Exposure Standards TWA	Liquefied Petroleum Gas = 1800 mg/m ³ . Cyclohexanone = 100 mg/m ³ . Propylene Glycol Mono Methyl Ether Acetate (PGMA) = 274 mg/m ³ .
Exposure Standards STEL	Liquefied Petroleum Gas = No data available Propylene Glycol Mono Methyl Ether Acetate (PGMA) = 822 mg/m ³ Skin
Engineering Controls	During the spray application period, ensure there is adequate ventilation at all times e.g. preferably with doors and windows open. Do not used in a confined space

PERSONAL PROTECTION

Inhalation AS –N.ZS 1715/16	The wearing of an Organic Vapour Respirator is recommended during the spray application period.
Eye AS –N.ZS 1337	The wearing of safety glasses fitted with side shields is recommended during the spray application period Do not wear contact lenses.
Gloves AS –N.ZS 2161	The wearing of Viton or PVC gloves is recommended during the spray application period.
Footwear AS –N.ZS 2210	The wearing of enclosed footwear is recommended during the spray application period.
Clothing AS –N.ZS 2919	The wearing of anti-static clothing made on natural or synthetic high temperature fibre is recommended during the spray application period.
Hearing AS –N.ZS 1270	Not required since the product is not applied by conventional spray
Other Requirements	Avoid contact with eyes and skin. Avoid inhaling spray mists and vapours.



PHYSICAL – CHEMICAL PROPERTIES

Appearance	A colourless liquid with a strong odour.
pH	Not required.
Vapour Pressure (Butyl Acetate = 1)	Greater than 1.0
Boiling Point °C	No data available
Density	0.84 {calculated value}
Solubility in water	Immiscible
Flash Point °C	< – 25 °C {literature value}
Flammability Limits	Lower Explosive Limit = No data available Upper Explosive Limit = No data available
Auto Ignition °C	250 °C {literature value}
Volatile Components	Liquefied Petroleum Gas, Cyclohexanone and Propylene Glycol Mono Methyl Ether Acetate.

STABILITY and REACTIVITY

Chemical Stability	Stable under normal conditions of use.
Conditions to avoid	Avoid contact with heat and all ignition sources.
Hazardous decomposition products	On heating, containers may rupture and explode: contents may burn rapidly forming toxic gases including carbon monoxide.
Incompatible materials	Incompatible with strong oxidizing agents
Hazardous Reactions	Will not polymerize.

TOXICOLOGICAL INFORMATION

Acute Toxicity Data

<i>Health Effects</i>	<i>Risk Phrase</i>	<i>Cyclohexanone</i>	<i>Liquefied Petroleum Gas</i>	<i>PGMA</i>
Inhalation LC ₅₀ rat 4 hours	20	8000ppm/4hr	> 20mgm/L	> 20mgm/L
Dermal LD ₅₀ rabbit	21	948 mgm/kg	> 2000 mgm/kg	7500 mgm/kg
Oral LD ₅₀ rat	22	1535 mgm/kg	> 2000 mgm/kg	8500 mgm/kg

Note

Risk phrases R20/21/22 has been assigned by the EEC Council Directive 67/548/EEC.
Risk Phrases R20/21/22 – Harmful by inhalation, skin contact or if swallowed.

Acute Oral Toxicity (Cyclohexanone and Propylene Glycol Mono Methyl Ether Acetate) rat	Low toxicity. Aspiration into lungs when swallowed or vomited may cause chemical pneumonitis which may be fatal.
Acute Dermal Toxicity (Cyclohexanone and Propylene Glycol Mono Methyl Ether Acetate)rabbit	Low toxicity.
Acute Inhalation Toxicity (Cyclohexanone and Propylene Glycol Mono Methyl Ether Acetate)rat	Low toxicity. High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea; continued inhalation may result in unconsciousness and/or death.

Health Effects

Inhalation	The inhalation of vapours and spray mist may cause acute irritation in the respiratory tract. Other symptoms may cause central nervous system depression resulting in headaches, dizziness, nausea, loss of co-ordination and impaired judgement.
Ingestion	May cause irritation
Eyes	Irritating to the eyes, including burning sensation, redness, swelling and/or blurred vision.
Skin	May cause irritation to the skin.
Carcinogenicity.	Not carcinogenic in animal studies.
Mutagenicity	Not mutagenic in animal studies
	May cause foetotoxicity in animals. Does not impair fertility.

ECOLOGICAL INFORMATION

Environment	Harmful to aquatic environment (R52). May cause long – term adverse effects in the aquatic environment (R53). Danger to ozone layer (R 59).
--------------------	---

DISPOSAL CONSIDERATIONS

Collect all residues and placed into labelled and sealed containers. Do not incinerate or puncture empty containers after use. Crush all small empty containers. Dampen all unwanted cloths and rags in water prior to disposal. Do not recycle contents or spent containers. Ensure all contents do not pollute waterways, drains and other water courses.

TRANSPORT INFORMATION

UN number	1950		
Proper Shipping Name	AEROSOLS – with a capacity less than 1 Litre		
Class	2.1	Subsidiary Risk	Not Required
Packing Group	Not Assigned		
Emergency Procedures		Initial Emergency Response Guide	49
HAZCHEM	2Y		
IMDG			



REGULATORY INFORMATION

SUSDP Classified as a Schedule S 5 poison.

OTHER INFORMATION

Emergency Contact **Poisons Information Centre 13 11 26** **HiChem Paint Technologies (03) 9796 3400**

Disclaimer *Data provided is to best of HiChem Paint Technologies Proprietary Limited knowledge and believe to be accurate and reliable as of the date of issued. However no expressed or implied warranties are given. HiChem Paint Technologies Proprietary Limited cannot anticipate or control the conditions under which this information may be used. Therefore, it is user's responsibility to satisfy themselves as to the suitability and completeness of such information for their particular use. It is the responsibility of the user to ensure that the issue is current. This information given is a non-controlled document*