

**HiChem Paint Technologies Pty.Ltd.**

A.B.N. 95 064 139 563  
73 Hallam South Road, HALLAM, VICTORIA 3803.  
Telephone : {03} 9796 3400      Facsimile : {03} 9796 4500  
Email: [msdsinfo@hichem.com.au](mailto:msdsinfo@hichem.com.au)      [www:hichem.com.au](http://www.hichem.com.au)



## IDENTIFICATION of the SUBSTANCE(S) and COMPOSITION

<b>Product Name</b>	2 PACK HIBUILD PRIMER FILLER	<b>Code</b>	HPF
<b>Product Use</b>	Part of a two pack, primer filler applied by spray onto automotive surfaces.		
<b>Ingredients</b>	<b>Name</b>	<b>CAS Number</b>	<b>Proportion w/w</b>
	Ethyl Benzene	100 – 41 – 4	1.0 – <10 %
	Xylene	1330 – 20 – 7	10 – <30 %
	Coloured Pigments/Extenders (Non-Hazardous)	Mixture	30 – 60 %
	Encapsulated Crystalline Silicon Dioxide	14807 – 96 – 6	1.0 – <10 %
	Polymeric Acrylic Resin	Not Known	10 – <30 %

## HAZARD IDENTIFICATION

The product is classified both as **Hazardous Substance** and **Dangerous Goods** in accordance to ASCC

**Risk Phrases R**

- 10 Flammable Liquid  
20/21/22 Harmful by inhalation, in contact with the skin and if swallowed.  
36/37/38 Irritating to eyes, the respiratory system and skin.  
40 Limited evidence of a carcinogenic effect.  
52/53 Harmful to aquatic systems and may cause long term adverse effects in the aquatic environment.  
63 Possible risk of harm of unborn child.  
65/66/67 Harmful. May cause lung damage if swallowed. Repeated or prolonged exposure may cause skin dryness and cracking Vapours may cause headaches, drowsiness and dizziness.

**Safety Phrases S**

- 2 Keep out of reach of children.  
7/9 Keep containers tightly closed when not in use and also in a well ventilated area.  
15 Keep away from heat.  
16/33 Keep away from sources of ignition. Take precautionary measures against static electricity.  
20/21 When using, do not eat, drink or smoke.  
23.5 Do not breathe the vapours and spray mists  
24/25 Avoid skin contact and with the eyes.  
26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
27 Take off immediately all contaminated clothing.  
28.1 In contact with the skin, wash immediately soap and plenty of water.  
36/37/38/39 Wear protective clothing, including knee high boots, elbow length gloves, positive pressure air supplied full face respirator including eye and face protection. Wear hearing protection when applied by conventional spray  
45 In case of accident, or if you feel unwell, seek medical advice immediately. Show the label where possible.  
62 If swallowed, do not induce vomiting: seek medical advice immediately. Show the label where possible.

**ADG** PAINT – immiscible in water, UN 1263, Class 3, Packing Group III,  
**Classification** HAZCHEM 3[Y].  
**SUSDP** Classified as a Schedule S 5 poison.

### FIRST AID MEASURES

<b><i>Inhalation</i></b>	If the applicator feels drowsy, dizzy, tired or experiencing headaches, remove the victim to the fresh air. Keep the victim warm and quiet until all symptoms subside.
<b><i>Ingestion</i></b>	If swallow, and only if the person is conscious, give water to drink. <b>DO NOT</b> induce vomiting; seek URGENT medical attention if frothing from the mouth occurs.
<b><i>Eyes</i></b>	If splashed into eyes, hold eyes open, irrigate copiously with clean water for at least 15 minutes. Seek immediate medical attention if any irritation occurs.
<b><i>Skin</i></b>	If skin contact occurs, remove contaminated clothing, and wash thoroughly with soap and plenty of water. Seek medical attention if any irritation occurs.
<b><i>First Aid Facilities</i></b>	Clean Water Supply, soap or skin cleaner, barrier cream, emergency showers and eye wash stations.
<b><i>Advice to Doctor</i></b>	If poisoning occurs, consult with the Poisons Information Centre {Telephone <b>13 11 26</b> }. Have a copy of this material safety data sheet or label available. Treat symptomatically as symptoms may be delayed for several hours after exposure.



### FIRE FIGHTING MEASURES

<b><i>Extinguishing Media and Requirements</i></b>	Carbon Dioxide {CO <sub>2</sub> }, alcohol resistant foam, dry chemical or water spray. <b>DO NOT</b> use water jets. Bund area with sand to prevent run – off entering waterways and drains.
<b><i>Fire Fighting Procedures &amp; Precautions</i></b>	Fire – fighters should wear Chemical Splash Suit with attached Self – Contained Breathing Apparatus and gloves. Evacuate all non fire–fighting personnel away from the area. Turn off all electricity and power supplies. Keep containers cool with water spray or water to prevent rupture or burning. Move away all containers and equipment from the direction of the fire, if safe to do so. Keep upwind.
<b><i>Flammability</i></b>	Flammable Liquid. Flash Point = 23 °C
<b><i>Hazardous Decomposition Products</i></b>	On heating, containers may rupture and explode: contents may burn rapidly forming toxic gases including carbon monoxide. .



### ACCIDENTAL RELEASE MEASURES

<b><i>Spills and Leaks</i></b>	Contain all spills and leaks. Avoid contamination with spilt material on surfaces. Remove all sources of ignition and <b>NO SMOKING</b> . Wear the recommended full body impervious clothing, gloves and breathing apparatus as per AS– NZ 1715/16. Keep upwind. Absorb all spilt contents onto sand or earth.
<b><i>Disposal</i></b>	Collect all residues into labelled and sealed containers for disposal via special waste collection services as per local Statutory Authority requirements.
<b><i>Other Precautions</i></b>	Avoid contaminating waterways, drains, water courses and sewage.



## HANDLING and STORAGE

**Handling**

Keep out of reach of children. Avoid unnecessary contact with the material. After use before eating, drinking or smoking wash all exposed skin with soap and water.

**Storage**

Containers must be clearly labelled, rigid and strong. Store upright in a cool, dry, well ventilated area from heat, ignition sources and direct sunlight e.g. Flammable Goods Store as per AS 1940 requirements.

## EXPOSURE CONTROLS

**Exposure**

Aliphatic Esters = Not Known

Ethyl Benzene = 440 mg/m<sup>3</sup>.

**Standards MAK**

Xylene = 350 mg/m<sup>3</sup>.

**Exposure**

Xylene = 655 mg/m<sup>3</sup>.

**Standards STEL****Engineering**

When mixing and spraying of both 2 Pack HiBuild Primer Filler and the corresponding Isocyanate Hardener, all work must be performed out in approved spray booth in accordance with Australian Standard AS/NZS 4114.

**Controls**

## PERSONAL PROTECTION

**Inhalation**

**AS –NZS**

**1715/16**

The wearing of Positive Pressure Air Supplied Full Face Respirator **must be** worn at all times during the mixing and spray application period; until all spray mists are efficiently dispersed from the spray booth atmosphere before exiting.

**Eye**

**AS –NZS 1337**

The wearing of safety glasses fitted with side shields **must be** worn at all times during the mixing and spray application period. Do not wear contact lenses.

**Gloves**

**AS –NZS 2161**

The wearing of Viton or PVC gloves **must be** worn at all times during the mixing and spray application period.

**Footwear**

**AS –NZS 2210**

The wearing of enclosed footwear **must be** worn at all times during the mixing and spray application period

**Clothing**

**AS –NZS 2919**

The wearing of anti-static clothing made on natural or synthetic high temperature fibre **must be** worn at all times during the mixing and spray application period

**Hearing**


**AS –NZS 1270**

The wearing of hearing protection when applying by conventional spray **must be** worn during the spraying application period

**Other**

**Requirements**

Avoid contact with eyes and skin. Avoid inhaling spray mists and vapours at all times



## PHYSICAL – CHEMICAL PROPERTIES

<b>Appearance</b>	A coloured liquid with a mild odour.	
<b>pH</b>	Not required.	
<b>Vapour Pressure</b> (Butyl Acetate = 1)	Equal to 1.	
<b>Boiling Point °C</b>	127 – 145 °C {literature value}	
<b>Density</b>	1.46 {calculated value}	
<b>Solubility in water</b>	Immiscible	
<b>Flash Point °C</b>	23 °C {literature value}	
<b>Flammability</b>	Lower Explosive Limit = 1.0 %	Upper Explosive Limit = 11.5 %
<b>Limits</b>		
<b>Auto Ignition °C</b>	430 °C {literature value}	
<b>Volatile</b>	Organic Solvents	
<b>Components</b>		

## STABILITY and REACTIVITY

<b>Chemical Stability</b>	Stable under normal conditions of use.
<b>Conditions to avoid</b>	Avoid contact with heat and all ignition sources.
<b>Hazardous decomposition products</b>	On heating, containers may rupture and explode: contents may burn rapidly forming toxic gases including carbon monoxide, cyanides and oxides of nitrogen.
<b>Incompatible materials</b>	Incompatible with strong oxidizing agents
<b>Hazardous Reactions</b>	Will not polymerize.

## TOXICOLOGICAL INFORMATION

<b>Health Effects</b>	<b>Risk</b>	<b>Aliphatic Esters</b>	<b>Ethyl Benzene</b>	<b>Xylene</b>
<b>TWA</b>	<b>Phrase</b>			
Inhalation LC <sub>50</sub> rat 4 hours	20	> 20 mgm/kgm	> 20 mgm/kgm	> 20 mgm/kgm
Dermal LD <sub>50</sub> rabbit	21	>2000 mgm/kg	>2000 mgm/kg	4500 mgm/kg
Oral LD <sub>50</sub> rat	22	>2000 mgm/kg	>2000 mgm/kg	4300 mgm/kg

### Note

Risk phrases R23, R20/21/22 has been assigned by the EEC Council Directive 67/548/EEC. Risk Phrase R23 – Toxic by inhalation.

Risk Phrases R20/21/22 – Harmful by inhalation, skin contact or if swallowed.

Acute Oral Toxicity rat	Low toxicity. Aspiration into lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.
Acute Dermal Toxicity rabbit	Low toxicity.
Acute Inhalation Toxicity rat	Low toxicity. High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea; continued inhalation may result in unconsciousness and/or death.

**TOXICOLOGICAL INFORMATION (CONTINUED)****Health Effects**

Inhalation	The inhalation of vapours and spray mist may cause acute irritation and sensitization to the respiratory system leading to an asthmatic condition, wheeziness and tightness of the chest. When sensitized persons may subsequently show asthmatic symptoms when exposed to atmospheric concentrations well below the Occupational Exposure Limit (OEL). Repeated or prolonged exposure may lead to permanent disability. Other symptoms may cause central nervous system depression resulting in headaches, dizziness, nausea, loss of co-ordination, impaired judgement. Delayed reactions possible (breathing difficulties, coughs, asthma).
Ingestion	Large quantities may cause nausea and vomiting.
Eyes	Irritating to the eyes, including burning sensation, redness, swelling and/or blurred vision. Also, may cause decreased in colour perception..
Skin	May have degreasing effect on the skin may result in contact dermatitis.
Other Data	Limited evidence of a carcinogenic effect Not mutagenic in animal studies Does not impair fertility. Causes foetotoxicity in animals at doses which are maternally toxic.

**ECOLOGICAL INFORMATION**

<b>Environment</b>	Harmful to aquatic environment (R52). May cause long – term adverse effects in the aquatic environment (R53).
--------------------	--

**DISPOSAL CONSIDERATIONS**

Collect all residues and placed into labelled and sealed containers. Do not incinerate empty containers after use. Dampen all unwanted cloths and rags in water prior to disposal. Do not recycle contents or spent containers. Crush all small empty containers. Larger containers and drums may be sent to an approved drum recycler. Ensure all contents do not pollute waterways, drains and other water courses.

**TRANSPORT INFORMATION**

<b>UN number</b>	1263		
<b>Proper Shipping Name</b>	PAINT – immiscible in water		
<b>Class</b>	3	<b>Subsidiary Risk</b>	Not Required
<b>Packing Group</b>	III		
<b>Emergency Procedures</b>	EP 3305	<b>Initial Emergency Response Guide</b>	15
<b>HAZCHEM</b>	3[Y]		
<b>IMDG</b>			

**REGULATORY INFORMATION**

<b>SUSDP Classification</b>	Classified as a Schedule S 5 Poison.
-----------------------------	--------------------------------------

**OTHER INFORMATION**

**Emergency  
Contact  
Disclaimer**

**Poisons Information Centre 13 11 26**

**HiChem Paint Technologies  
(03) 9796 3400**

*Data provided is to best of HiChem Paint Technologies Proprietary Limited knowledge and believe to be accurate and reliable as of the date of issued. However no expressed or implied warranties are given. HiChem Paint Technologies Proprietary Limited cannot anticipate or control the conditions under which this information may be used. Therefore, it is user's responsibility to satisfy themselves as to the suitability and completeness of such information for their particular use. It is the responsibility of the user to ensure that the issue is current. This information given is a non-controlled document*