

HiChem Paint Technologies Pty Ltd

A.B.N. 95 064 139 653

73 Hallam South Road, HALLAM, VICTORIA 3803.

Telephone : {03} 9796 3400

Facsimile : {03} 9796 4500

Email: msdsinfo@hichem.com.auWebsite: www.hichem.com.au**IDENTIFICATION of the SUBSTANCE(S) and COMPOSITION**

Product Name	ISO FREE FINISH– LEAD CONTAINING TINTERS	Code	IF –
Product Use	Use for tinting of colours in isocyanate–free automotive spraying finish		
Ingredients	Name	CAS Number	Proportion w/w
	Lead Chromate (as Lead)	7758–97–6	10 – 30 %
	Lead Chromate (as Chromium)	7758–97–6	1 – 10 %
	Xylene	1330–20–7	10 – 30 %
	Butyl Acetate	123–86–4	10 – 30 %
	Synthetic Resins (Non–Hazardous)	Not Known	30 – 60 %
	Additives (Non–Hazardous)	Not Known	1 – 10 %

HAZARD IDENTIFICATION

Hazard Classification	Hazardous Substance, Dangerous Goods		
Chronic Risk	33,40,61,62, 65,66,67	Danger of cumulative effects. Limited evidence of a carcinogenic effect. May cause harm to unborn child. Possible risk of impaired fertility. Harmful. May cause lung damage if swallowed. Repeated exposure may cause skin dryness and cracking. Vapours may cause headaches, drowsiness and dizziness.	
Acute			
Skin Risk	21,38	Harmful X _n , Irritant X _i	
Inhalation Risk	20,37	Harmful X _n Irritant X _i	
Ingestion Risk	22	Harmful X _n	
Eyes Risk	36	Irritant X _i	
ADG Classification	PAINT RELATED MATERIAL –TINTERS, immiscible in water, UN 1263, Class 3, Packing Group III, HAZCHEM 3[Y].		
SUSDP Classification	Classified as a Schedule S 6 poison.		

FIRST AID MEASURES

Inhalation	If the applicator feels drowsy, dizzy, tired or experiencing headaches, remove the victim to the fresh air. Keep the victim warm and quiet until all symptoms subside.
Ingestion	If swallowed and only if the person is conscious, give water to drink. DO NOT induce vomiting. Seek URGENT medical attention if frothing from the mouth occurs.
Eyes	If splashed into eyes, hold eyes open, irrigate copiously with clean water for at least 15 minutes. Seek immediate medical attention if any irritation occurs.
Skin	If skin contact occurs, remove contaminated clothing, and wash thoroughly with soap and plenty of water. Seek medical attention if any irritation occurs.
First Aid Facilities	Clean Water Supply, soap or skin cleaner, barrier cream, emergency showers and eye wash stations.
Advice to Doctor	If poisoning occurs, consult with the Poisons Information



Centre {Telephone **13 11 26**}. Have a copy of this material safety data sheet or label available. Treat symptomatically.

FIRE FIGHTING MEASURES

Extinguishing Media and Requirements Fire Fighting Procedures & Precautions

Carbon Dioxide {CO₂}, alcohol resistant foam, dry chemical or water spray. **DO NOT** use water jets. Bund area with sand to prevent run – off entering waterways and drains. Fire – fighters should wear Chemical Splash Suit with attached Self – Contained Breathing Apparatus and gloves. Evacuate all non fire–fighting personnel away from the area. Turn off all electricity and power supplies. Keep containers cool with water spray or water to prevent rupture or burning. Move away all containers and equipment from the direction of the fire, if safe to do so. Keep upwind.



Flammability Hazardous Decomposition Products

Flammable Liquid. Flash Point = 24°C
On heating, containers may rupture and explode: contents may burn rapidly forming toxic gases including carbon monoxide.

ACCIDENTAL RELEASE MEASURES

Spills and Leaks

Contain all spills and leaks. Avoid contamination with spilt material on surfaces. Remove all sources of ignition and **NO SMOKING**. Wear the recommended full body impervious clothing, gloves and breathing apparatus as per AS– NZ 1715/16. Keep upwind. Absorb all spilt contents onto sand or earth.



Disposal

Collect all residues into labelled and sealed containers for disposal via special waste collection services as per local Statutory Authority requirements.

Other Precautions

Avoid contaminating waterways, drains, water courses and sewage.

HANDLING and STORAGE

Handling

Keep out of reach of children. Avoid unnecessary contact with the material. After use before eating, drinking or smoking wash all exposed skin with soap and water.

Storage

Containers must be clearly labelled, rigid and strong. Store upright in a cool, dry, well ventilated area from heat, ignition sources and direct sunlight e.g. Flammable Goods Store as per AS 1940 requirements.

EXPOSURE CONTROLS

Exposure Standards MAK Engineering Controls

Butyl Acetate = 480 mg/m³.

Xylene = 440 mg/m³.

Lead = 0.15 mg/m³.

Chromium = 0.05 mg/m³.

When applying the product, ensure there is adequate ventilation during the application period.

PERSONAL PROTECTION

Inhalation

AS –NZS 1715/16

Eye

AS –NZS 1337

Gloves

AS –NZS 2161

Footwear

AS –NZS 2210

Clothing

AS –NZS 2919

Hearing

AS –NZS 1270

Other Requirements

The wearing of Organic Vapour Respirator is recommended when tinting to desired colour.

The wearing of safety glasses fitted with side shields is recommended when tinting to desired colour. Do not wear contact lenses.


The wearing of Viton or PVC gloves is recommended when tinting to desired colour.

The wearing of enclosed footwear is recommended when tinting to desired colour.

The wearing of anti-static clothing made on natural or synthetic high temperature fibre is recommended when tinting to desired colour.

Not Required.

Avoid contact with eyes and skin. Wear the recommended Personal Protective Equipment as described.



PHYSICAL – CHEMICAL PROPERTIES

Appearance

A coloured liquid with a sweet odour.

pH

Not required.

Vapour Pressure

Greater than 1.

(Butyl Acetate = 1)

Boiling Point °C

108 – 175 °C {literature value}

Density

1.0 – 1.3 {depending on final colour}

Solubility in water

Immiscible

Flash Point °C

24°C {literature value}

Flammability Limits

Lower Explosive Limit = 1.0%

Upper Explosive Limit = 12.0%

Auto Ignition °C

370°C {literature value}

Volatile Components

Organic Solvents

STABILITY and REACTIVITY

Chemical Stability

Stable under normal conditions of use.

Hazardous

Will not polymerize.

Polymerization

Conditions to avoid

Avoid contact heat and all ignition sources.

Incompatible materials

Incompatible with strong oxidizing agents

Hazardous decomposition products

Stable.

TOXICOLOGICAL INFORMATION

Inhalation

LC₅₀

rat Organic Solvents > 20mg/Litre for 4 hours

Skin

LD₅₀

rabbit Organic Solvents > 400 mg/kilogram bodyweight/day

Ingestion

LD₅₀

rat Organic Solvents, Lead Chromate > 200 mg/kilogram bodyweight/day

Eyes

Organic Solvents – irritant

Sensitization

No data for Organic Solvents – non sensitizer

ECOLOGICAL INFORMATION

Environment R53 May cause long – term adverse effects in aquatic environment.

DISPOSAL CONSIDERATIONS

Collect all residues and placed into labelled and sealed containers. Do not incinerate empty containers after use. Dampen all unwanted cloths and rags in water prior to disposal. Do not recycle contents or spent containers. Crush all small empty containers. Larger containers and drums may be sent to an approved drum recycler. Ensure all contents do not pollute waterways, drains and other water courses.

TRANSPORT INFORMATION

UN number	1263		
Proper Shipping Name	PAINT RELATED MATERIAL – TINTERS	immiscible	
Class	3	Subsidiary Risk	Not Required
Packing Group	III		
Emergency Procedures	EP 3303	Initial Emergency Response Guide	15
HAZCHEM	3[Y]		
IMDG			

**REGULATORY INFORMATION**

Risk Phrases R	33,40,61,62, 65,66,67	Danger of cumulative effects. Limited evidence of a carcinogenic effect. May cause harm to unborn child. Possible risk of impaired fertility. Harmful. May cause lung damage if swallowed. Repeated exposure may cause skin dryness and cracking. Vapours may cause headaches, drowsiness and dizziness.
	20/21/22	Harmful by inhalation, skin contact and if swallowed.
	36/37/38	Irritating to eyes, respiratory tract and skin.
	10	Flammable
Safety Phrases S	7/9	Keep containers closed and in a well ventilated area when not in use.
	23.2	Avoid breathing vapours.
	24/25	Avoid contact with skin and eyes.
	36/37/38/39	Wear recommended Personal Protective Equipment – protective clothing, gloves, boots, respirator and eye protection.
SUSDP Classification	The current product is labelled as Schedule 6 Poison. Contains 30% Lead (maximum) and 10% Chromium (maximum).	

OTHER INFORMATION

Emergency Contact **Poisons Information Centre 13 11 26** **HiChem Paint Technologies (03) 9796 3400**

Disclaimer *Data provided is to best of HiChem Paint Technologies Proprietary Limited knowledge and believe to be accurate and reliable as of the date of issued. However no expressed or implied warranties are given. HiChem Paint Technologies Proprietary Limited cannot anticipate or control the conditions under which this information may be used. Therefore, it is user's responsibility to satisfy themselves as to the suitability and completeness of such information for their particular use. It is the responsibility of the user to ensure that the issue is current. This information given is a non-controlled document*