

HiChem Paint Technologies Pty.Ltd.

A.B.N. 95 064 139 563

73 Hallam South Road, HALLAM, VICTORIA 3803.

Telephone : {03} 9796 3400

Facsimile : {03} 9796 4500

Email:msdsinfo@hichem.com.au

www:hichem.com.au

**HAZARD IDENTIFICATION**

The product is classified as both **Dangerous Goods** and **Hazardous Substance** in accordance to Work Safe Australia criteria.

Risk Phrases R

- 12 Extremely Flammable Gas
 21/22 Harmful in contact with skin and if swallowed.
 36/37/38 Irritating to the eyes, respiratory system and skin.
 40 Limited evidence of a carcinogenic effect.
 48/20 Harmful: Danger of serious damage to health by prolonged exposure through inhalation.
 52/53/59 Harmful to aquatic organisms and may cause long term adverse effects in the aquatic environment. Dangerous for the ozone layer
 65/66/67 Harmful. May cause lung damage if swallowed. Repeated or prolonged exposure may cause skin dryness and cracking Vapours may cause headaches, drowsiness and dizziness.

Safety Phrases S

- 2 Keep out of reach of children.
 7/9 Keep containers tightly closed when not in use and also in a well ventilated area.
 15/16/33 Keep away from heat and sources of ignition. Take precautionary measures against static electricity.
 20/21 When using, do not eat, drink or smoke.
 23.5 Do not breathe the vapours or spray mist
 24/25 Avoid skin contact and with the eyes.
 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
 27 Take off immediately all contaminated clothing.
 28.1 In contact with the skin, wash immediately soap and plenty of water.
 36/37/38/39 Wear protective clothing, including enclosed footwear, PVC or Neoprene gloves, organic vapour/particulate respirator including eye, hair and face protection
 45 In case of accident, or if you feel unwell, seek medical advice immediately. Show the label where possible.
 62 If swallowed, do not induce vomiting: seek medical advice immediately. Show the label where possible.

ADG AEROSOLS – with a capacity less than 1 Litre, UN 1950, HAZCHEM 2 Y, Class 9,

Classification Initial Emergency Response Guide 49.

SUSDP Classified as a Schedule S 5 poison.

IDENTIFICATION of the SUBSTANCE(S) and COMPOSITION

| Product Name | SANDABLE PRIMER – AEROSOL | | Code PR |
|---------------------|---|-------------------|-----------------------|
| Product Use | An aerosol spray used for “touch – up” of small automotive areas. | | |
| Ingredients | Name | CAS Number | Proportion w/w |
| | Liquefied Petroleum Gas | 68746 – 85 – 7 | 30 – 60 % |
| | Acetone | 67 – 64 – 1 | 30 – 60 % |
| | Ethyl Benzene | 100 – 41 – 4 | 1.0 – <10.0 % |
| | Xylene | 1330 – 20 – 7 | 1.0 – <10.0 % |
| | Coloured Pigments/Extenders(Non – Hazardous) | Mixture | 1.0 – <10.0 % |
| | Polymeric Synthetic Resins(Non – Hazardous) | Proprietary | 1.0 – <10.0 % |
| | Additives (Non – Hazardous) | Mixture | 1.0 – <10.0 % |

FIRST AID MEASURES

| | |
|------------------------------------|--|
| <i>Inhalation</i> | If the applicator feels drowsy, dizzy, tired or experiencing headaches, remove the victim away from the contaminated area to the fresh air. Keep the victim warm and quiet until all symptoms subside. If the victim is not breathing, apply artificial respiration immediately away from the contaminated area. |
| <i>Ingestion</i> | Unlikely route of exposure. If swallow, and only if the person is conscious, give water to drink. DO NOT induced vomiting; seek URGENT medical attention if frothing from the mouth occurs. |
| <i>Eyes</i> | If splashed into eyes, hold eyelids apart, and flush the eyes continuously with running for at least 15 minutes. Continue flushing until advised by a doctor. |
| <i>Skin and Hair</i> | If skin and hair contact occurs, remove contaminated clothing, and wash thoroughly with soap and plenty of water. Continue flushing until advised by a doctor. |
| <i>First Aid Facilities</i> | Clean Water Supply, soap or skin cleaner, barrier cream, emergency showers and eye wash stations. |
| <i>Advice to Doctor</i> | If poisoning occurs, consult with the Poisons Information Centre {Telephone 13 11 26 }. Have a copy of this material safety data sheet or label available. Treat symptomatically as symptoms may be delayed for several hours after exposure. |



FIRE FIGHTING MEASURES

| | |
|--|---|
| <i>Extinguishing Media and Requirements</i> | Carbon Dioxide {CO ₂ }, alcohol resistant foam, dry chemical or water spray. DO NOT use water jets. Bund area with sand to prevent run – off entering waterways, sewage and drains. |
| <i>Hazardous Decomposition Products</i> | On heating, containers may rupture and explode: contents may burn rapidly forming toxic gases including carbon monoxide, soot and smoke, above the boiling point |
| <i>Flammability</i> | Highly Flammable Gas. Flash Point = <- 25 °C |
| <i>Specific Hazards</i> | Vapours may form explosive/air mixtures. |
| <i>Precautions in connection with Fire</i> | Fire – fighters should wear Chemical Splash Suit with attached Self – Contained Breathing Apparatus and gloves. Evacuate all non fire–fighting personnel away from the area. Turn off all electricity and power supplies. Keep containers cool with water spray or water to prevent rupture or burning. Move away all packages and equipment from the direction of the fire, if safe to do so. Keep upwind. |



ACCIDENTAL RELEASE MEASURES

| | |
|---|---|
| Emergency Procedures. Spills and Leaks | Contain all spills and leaks. Avoid contamination with spilt material on surfaces or entering waterways, drains and sewage. Remove all sources of ignition and NO SMOKING . Wear the recommended full body impervious clothing, gloves and breathing apparatus as per AS– NZ 1715/16. Keep upwind. Absorb all spilt contents onto sand or earth. |
| Disposal | Collect all residues into labelled and sealed containers for disposal via special waste collection services as per local Statutory Authority requirements. |
| Other Precautions | Ensure there is adequate ventilation at all times during the cleaning up period. |



HANDLING and STORAGE


| | |
|--------------------------------------|---|
| Precautions for Safe Handling | Highly Flammable Gas. Remove all sources of ignition. Wear the recommended Personal Protective Equipment including organic vapour respirator, eye/face protection, protective clothing, gloves and enclosed footwear. Ensure there is adequate ventilation at all times. After use, before eating, drinking or smoking, wash all exposed skin and hair with soap and water. |
| Conditions of Safe Storage | Containers must be clearly labelled, rigid and strong. Store upright in a cool, dry, well ventilated area from heat, ignition sources and direct sunlight e.g. Flammable Goods Store as per AS 1940 requirements. |

EXPOSURE CONTROLS

| | | |
|----------------------------------|---|---|
| Exposure Standards MAK | Acetone = 1200 mg/m ³ . | Ethyl Benzene = 440 mg/m ³ . |
| Exposure Standards STEL | Xylene = 350 mg/m ³ . | |
| Biological Limited Values | Xylene = 655 mg/m ³ . | |
| Engineering Controls | There are no known Biological Limited Values have been assigned. | |
| | The use of local exhaust ventilation equipment is required. All ventilation equipment must be fitted with flame and explosion proof electrical fittings. Do not use in a confined area. | |

PERSONAL PROTECTION

| | |
|---|---|
| Inhalation <i>AS –NZS 1715/16</i> | The wearing of Organic Vapour/Particulate Respirator should be worn at all times during the handling and application period. |
| Eye <i>AS –NZS 1337</i> | The wearing of safety glasses fitted with side shields should be worn at all times during the handling and application period. Do not wear contact lenses. |
| Gloves <i>AS –NZS 2161</i> | The wearing of Neoprene or PVC gloves should be worn at all times during the handling and application period. |
| Footwear <i>AS –NZS 2210</i> | The wearing of enclosed footwear should be worn at all times during the handling and application period |
| Clothing <i>AS –NZS 2919</i> | The wearing of anti-static clothing made on natural or synthetic high temperature fibre should be worn at all times during the handling and application period |
| Hearing <i>AS –NZS 1270</i> | Not required. |
| Other Requirements | Avoid contact with eyes and skin. Avoid inhaling vapours and spray mists at all times |



PHYSICAL – CHEMICAL PROPERTIES

| | | |
|--|-------------------------------------|-----------------------------|
| Appearance | A coloured gas with a strong odour. | |
| pH | Not required. | |
| Vapour Pressure <i>(Butyl Acetate = 1)</i> | Greater than 1 | |
| Boiling Point °C | <0 – 145 °C (literature value) | |
| Density | 0.83 (calculated value) | |
| Solubility in water | Immiscible | |
| Flash Point °C | < - 25 °C (literature value) | |
| Flammability Limits | Lower Explosive Limit = 1.0 | Upper Explosive Limit = 8.0 |
| Auto Ignition °C | 250 °C (literature value) | |
| Volatile Components | Liquid Hydrocarbons, ketones. | |

STABILITY and REACTIVITY

| | |
|---|--|
| Chemical Stability | Stable under normal conditions of use. |
| Conditions to avoid | Avoid contact with heat, all ignition sources and static electricity |
| Hazardous decomposition products | On heating, containers may rupture and explode: contents may burn rapidly forming toxic gases including carbon monoxide. |
| Incompatible materials | Incompatible with strong oxidizing agents |
| Hazardous Reactions | Will not polymerize since the product is supplied as a polymeric coating. |

TOXICOLOGICAL INFORMATION

| <i>Health Effects</i> | <i>Risk Phrase</i> | <i>Acetone</i> | <i>Ethyl Benzene</i> | <i>Xylene</i> |
|------------------------------------|--|------------------------------|------------------------|------------------------|
| Inhalation LC ₅₀ rat | 20 | 32000 mg/m ³ . | 20 mg/m ³ . | 20 mg/m ³ . |
| Dermal LD ₅₀ rabbit | 21 | 20000 mgm/kg | 2000 mgm/kg | 4500 mgm/kg |
| Oral LD ₅₀ rat | 22 | 5800 mgm/kg | 2000 mgm/kg | 4300 mgm/kg |
| Acute Oral Toxicity rat | Low toxicity. Aspiration into lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal. | | | |
| Acute Dermal Toxicity rabbit | Low toxicity. | | | |
| Acute Inhalation Toxicity rat | Low toxicity. High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea; continued inhalation may result in unconsciousness and/or death. | | | |

TOXICOLOGICAL INFORMATION (CONTINUED)

Health Effects

| | |
|--------------------------|--|
| Inhalation | The inhalation of vapours and may cause acute irritation to the respiratory system. Other symptoms may cause central nervous system depression resulting in headaches, dizziness, nausea, loss of co-ordination, impaired judgement. Vapours may cause headaches, drowsiness and dizziness |
| Ingestion | Large quantities may cause nausea and vomiting. Harmful. May cause lung damage if swallowed. |
| Eyes | May irritate to the eyes, including burning sensation, redness, swelling and/or blurred vision. Also, may cause decreased in colour perception. |
| Skin | May have degreasing effect on the skin may result in contact dermatitis. Repeated or prolonged exposure may cause skin dryness and cracking. |
| Carcinogenic | Limited evidence of a carcinogenic effect |
| Mutagenic | Not mutagenic in animal studies. |
| Reproductive Toxicity | No data available |

ECOLOGICAL INFORMATION

| | |
|---------------------------------------|--|
| Environment | Harmful to aquatic organisms (R 52) May cause long – term adverse effects in the aquatic environment (R53). Danger to the ozone layer (R 59) |
| Persistence/ Degradability | No data available. |
| Mobility | No data available |
| Environment Protection | Not Known |



DISPOSAL CONSIDERATIONS

Collect all residues and placed into labelled and sealed containers. Do not incinerate empty aerosol containers after use. Dampen all unwanted cloths and rags in water prior to disposal. Do not recycle contents. Crush all small empty aerosol containers. Ensure all contents do not pollute waterways, drains and sewage.

TRANSPORT INFORMATION

| | | | |
|-----------------------------|--------------------------------------|---|--------------|
| UN number | 1950 | | |
| Proper Shipping Name | AEROSOL – capacity less than 1 Litre | | |
| Class | 9 | Subsidiary Risk | Not Required |
| Packing Group | Not Assigned | | |
| Emergency Procedures | EP 3900 | Initial Emergency Response Guide | 49 |
| HAZCHEM | 2 Y | | |
| IMDG | Not Known | | |



REGULATORY INFORMATION

| | |
|---|--|
| Regulatory Information and Hazard Category | The product is classified as a Hazardous Substance in accordance to Work Safe Australia as Harmful and Irritant. |
| SUSDP Classification | Classified as a Schedule S 5 Poison. |

OTHER INFORMATION

| | | |
|--------------------------|--|----------------------------------|
| Emergency Contact | Poisons Information Centre 13 11 26 | HiChem Paint Technologies |
| Disclaimer | | (03) 9796 3400 |

Data provided is to best of HiChem Paint Technologies Proprietary Limited knowledge and believe to be accurate and reliable as of the date of issued. However no expressed or implied warranties are given. HiChem Paint Technologies Proprietary Limited cannot anticipate or control the conditions under which this information may be used. Therefore, it is user's responsibility to satisfy themselves as to the suitability and completeness of such information for their particular use. It is the responsibility of the user to ensure that the issue is current. This information given is a non-controlled document

