

**HiChem Paint Technologies Pty.Ltd.**

A.B.N. 95 064 139 653

73 Hallam South Road, HALLAM, VICTORIA 3803.

Telephone : {03} 9796 3400

Facsimile : {03} 9796 4500

Email:msdsinfo@hichem.com.au

www:hichem.com.au



## IDENTIFICATION of the SUBSTANCE(S) and COMPOSITION

<b>Product Name</b>	QUICK DRY SUPER ENAMEL – AEROSOL	<b>Code</b>	QD
<b>Product Use</b>	Use as a “touch – up” for small areas		
<b>Ingredients</b>	<b>Name</b>	<b>CAS Number</b>	<b>Proportion w/w</b>
	Toluene	108 – 88 – 3	10 – <30 %
	Solvent Naphtha Light Aromatic	64742 – 95 – 6	10 – <30 %
	Liquefied Petroleum Gas	68746 – 85 – 7	30 – 60 %
	Colour Pigments/Extenders (Non – Hazardous)	Mixture	10 – <30 %
	Synthetic Resin (Non – Hazardous)	Proprietary	10 – <30 %
	Additives (Non – Hazardous)	Mixture	1 – <10 %

## HAZARD IDENTIFICATION

The product is classified both as **Hazardous Substance** and **Dangerous Goods** in accordance to ASCC

**Risk Phrases R**

12	Extremely Flammable Gas
48,20.	Harmful: danger of serious to health by prolonged exposure by inhalation.
21/22	Harmful in contact with the skin contact and if swallowed.
36/37/38	Irritating to the eyes, respiratory system and skin.
40	Limited evidence of a carcinogenic effect.
51/53/59	Toxic to aquatic organisms and may cause long term adverse effects in the aquatic environment. Dangerous to ozone layer.
63	Possible risk of harm of unborn child.
65/66/67	Harmful. May cause lung damage if swallowed. Repeated or prolonged exposure may cause skin dryness and cracking. Vapours may cause headaches, drowsiness and dizziness.

**Safety Phrases S**

2	Keep out of reach of children.
7/9	Keep containers tightly closed when not in use and also in a well ventilated area.
15	Keep away from heat.
16/33	Keep away from sources of ignition. Take precautionary measures against static electricity.
20/21	When using, do not eat, drink or smoke.
23.5	Do not breathe the vapours and spray mists
24/25	Avoid skin contact and with the eyes.
26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
27	Take off immediately all contaminated clothing.
28.1	In contact with the skin, wash immediately soap and plenty of water.
36/37/38/39	Wear protective clothing, including knee high boots, elbow length gloves, organic vapour – particulate respirator including eye and face protection.
45	In case of accident, or if you feel unwell, seek medical advice immediately. Show the label where possible.
57	Use appropriate containment to avoid environmental contamination.
62	If swallowed, do not induce vomiting: seek medical advice immediately. Show the label where possible.

**ADG Classification** AEROSOLS – with a capacity less than 1 Litre, UN 1950, Class 2.1, HAZCHEM 2Y.

**SUSDP** Classified as a Schedule S 5 poison.

### FIRST AID MEASURES

<b><i>Inhalation</i></b>	If the applicator feels drowsy, dizzy, tired or experiencing headaches, remove the victim to the fresh air. Keep the victim warm and quiet until all symptoms subside.
<b><i>Ingestion</i></b>	Unlikely route of exposure. Give 2 glasses of water to drink. If any systems occur, clean <b>DO NOT</b> induce vomiting; seek URGENT medical attention if frothing from the mouth occurs.
<b><i>Eyes</i></b>	If splashed into eyes, hold eyes open, irrigate copiously with clean water for at least 15 minutes. Seek immediate medical attention if any irritation occurs.
<b><i>Skin</i></b>	If skin contact occurs, remove contaminated clothing, and wash thoroughly with soap and plenty of water. Seek medical attention if any irritation occurs.
<b><i>First Aid Facilities</i></b>	Clean Water Supply, soap or skin cleaner, barrier cream, emergency showers and eye wash stations.
<b><i>Advice to Doctor</i></b>	If poisoning occurs, consult with the Poisons Information Centre {Telephone <b>13 11 26</b> }. Have a copy of this material safety data sheet or label available.



### FIRE FIGHTING MEASURES

<b><i>Extinguishing Media and Requirements</i></b>	Carbon Dioxide {CO <sub>2</sub> }, alcohol resistant foam, dry chemical or water spray. <b>DO NOT</b> use water jets. Bund area with sand to prevent run – off entering waterways and drains.
<b><i>Fire Fighting Procedures &amp; Precautions</i></b>	Fire – fighters should wear Chemical Splash Suit with attached Self – Contained Breathing Apparatus and gloves. Evacuate all non fire–fighting personnel away from the area. Turn off all electricity and power supplies. Keep containers cool with water spray or water to prevent rupture or burning. Move away all containers and equipment from the direction of the fire, if safe to do so. Keep upwind.
<b><i>Flammability Hazardous Decomposition Products</i></b>	Highly Flammable Gas. Flash Point =< – 25 °C On heating, containers may rupture and explode: contents may burn rapidly forming toxic gases including carbon monoxide. .



### ACCIDENTAL RELEASE MEASURES

<b><i>Spills and Leaks</i></b>	Contain all spills and leaks. Avoid contamination with spilt material on surfaces. Remove all sources of ignition and <b>NO SMOKING</b> . Wear the recommended full body impervious clothing, gloves and breathing apparatus as per AS– NZ 1715/16. Keep upwind. Absorb all spilt contents onto sand or earth.
<b><i>Disposal</i></b>	Collect all residues into labelled and sealed containers for disposal via special waste collection services as per local Statutory Authority requirements.
<b><i>Other Precautions</i></b>	Avoid contaminating waterways, drains, water courses and sewage.



### HANDLING and STORAGE


<b>Handling</b>	Keep out of reach of children. Avoid unnecessary contact with the material. After use before eating, drinking or smoking wash all exposed skin with soap and water.
<b>Storage</b>	Containers must be clearly labelled, rigid and strong. Store upright in a cool, dry, well ventilated area from heat, ignition sources and direct sunlight e.g. Flammable Goods Store as per AS 1940 requirements.

### EXPOSURE CONTROLS

<b>Exposure Standards MAK</b>	Liquefied Petroleum Gas = 1800 mg/m <sup>3</sup> .	Toluene = 190 mg/m <sup>3</sup> .
<b>Exposure Standards STEL</b>	Solvent Naphtha = Not Known	Liquefied Petroleum Gas = Not Known
<b>Engineering Controls</b>	Solvent Naphtha = Not Known	
	Toluene = 565 mg/m <sup>3</sup> .	
	During the spray application period, ensure there is adequate ventilation at all times e.g. preferably with doors and windows open. Do not used in a confined space	

### PERSONAL PROTECTION

<b>Inhalation</b> AS –NZZ 1715/16	The wearing of an Organic Vapour – Particulate Respirator <b>must be worn</b> during the application period.
<b>Eye</b> AS –NZZ 1337	The wearing of safety glasses fitted with side shields <b>must be worn</b> during the application period <b>Do not</b> wear contact lenses.
<b>Gloves</b> AS –NZZ 2161	The wearing of Viton or PVC gloves <b>must be worn</b> during the application period.
<b>Footwear</b> AS –NZZ 2210	The wearing of enclosed footwear <b>must be worn</b> during the application period.
<b>Clothing</b> AS –NZZ 2919	The wearing of anti–static clothing made on natural or synthetic high temperature fibre <b>must be worn</b> during the spray application period.
<b>Hearing</b> AS –NZZ 1270	Not required.
<b>Other Requirements</b>	Avoid contact with eyes and skin. Avoid inhaling spray mists and vapours.



### PHYSICAL – CHEMICAL PROPERTIES

<b>Appearance</b>	A coloured liquid with a mild odour.	
<b>pH</b>	Not required.	
<b>Vapour Pressure</b> (Butyl Acetate = 1)	Greater than 1.0	
<b>Boiling Point °C</b>	Not Known	
<b>Density</b>	0.90 {calculated value}	
<b>Solubility in water</b>	Immiscible	
<b>Flash Point °C</b>	< – 25 °C {literature value}	
<b>Flammability Limits</b>	Lower Explosive Limit = 1.0 %	Upper Explosive Limit = 13.0 %
<b>Auto Ignition °C</b>	250 °C {literature value}	
<b>Volatile Components</b>	Liquefied Petroleum Gas, Toluene and Solvent Naphtha as organic Solvents	

### STABILITY and REACTIVITY

<b>Chemical Stability</b>	Stable under normal conditions of use.
<b>Conditions to avoid</b>	Avoid contact with heat and all ignition sources.
<b>Hazardous decomposition products</b>	On heating, containers may rupture and explode: contents may burn rapidly forming toxic gases including carbon monoxide.
<b>Incompatible materials</b>	Incompatible with strong oxidizing agents
<b>Hazardous Reactions</b>	Will not polymerize.

### TOXICOLOGICAL INFORMATION

<i>Health Effects</i>	<i>Risk Phrase</i>	<i>Toluene</i>	<i>Liquefied Petroleum Gas</i>	<i>Solvent Naphtha</i>
Inhalation LC <sub>50</sub> rat	20	>20mgm/L	> 20mgm/L	> 20mgm/L
Dermal LD <sub>50</sub> rabbit	21	12100 mgm/kg	> 2000 mgm/kg	> 2000 mgm/kg
Oral LD <sub>50</sub> rat	22	640 mgm/kg	> 2000 mgm/kg	> 2000 mgm/kg

**Note**

Risk phrases R20/21/22 has been assigned by the EEC Council Directive 67/548/EEC.

Risk Phrases R20/21/22 – Harmful by inhalation, skin contact or if swallowed.

Acute Oral Toxicity	Moderately toxic. Aspiration into lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.
Acute Dermal Toxicity	Low toxicity.
Acute Inhalation Toxicity	Low toxicity. High concentrations may cause central nervous system depression resulting in headaches, dizziness, nausea, loss of co-ordination and impaired judgement; continued inhalation may result in unconsciousness and/or death

**Health Effects**

Inhalation	The inhalation of vapours and spray mist may cause acute irritation in the respiratory tract.
Ingestion	May cause irritation
Eyes	Irritating to the eyes, including burning sensation, redness, swelling and/or blurred vision.
Skin	Can have degreasing effect on the skin may result in contact dermatitis..
Carcinogenicity.	Limited evidence of a carcinogenic effect
Mutagenicity	Not mutagenic in animal studies Causes foetotoxicity in animals at doses which are maternally toxic. Does not impair fertility.

### ECOLOGICAL INFORMATION

<b>Environment</b>	Toxic to aquatic organisms (R51). May cause long – term adverse effects in the aquatic environment (R53). Danger to ozone layer (R 59).
--------------------	---

### DISPOSAL CONSIDERATIONS

Collect all residues and placed into labelled and sealed containers. Do not incinerate or puncture empty containers after use. Crush all small empty containers. Dampen all unwanted cloths and rags in water prior to disposal. Do not recycle contents or spent containers. Ensure all contents do not pollute waterways, drains and other water courses.



### TRANSPORT INFORMATION

<b>UN number</b>	1950		
<b>Proper Shipping Name</b>	AEROSOLS – with a capacity less than 1 Litre		
<b>Class</b>	2.1	<b>Subsidiary Risk</b>	Not Required
<b>Packing Group</b>	Not Assigned		
<b>Emergency Procedures</b>		<b>Initial Emergency Response Guide</b>	49
<b>HAZCHEM</b>	2Y		
<b>IMDG</b>			



### REGULATORY INFORMATION

**SUSDP** Classified as a Schedule S 5 poison.

### OTHER INFORMATION

<b>Emergency Contact</b>	<b>Poisons Information Centre 13 11 26</b>	<b>HiChem Paint Technologies</b> <b>(03) 9796 3400</b>
<b>Disclaimer</b>	<p><i>Data provided is to best of HiChem Paint Technologies Proprietary Limited knowledge and believe to be accurate and reliable as of the date of issued. However no expressed or implied warranties are given. HiChem Paint Technologies Proprietary Limited cannot anticipate or control the conditions under which this information may be used. Therefore, it is user's responsibility to satisfy themselves as to the suitability and completeness of such information for their particular use. It is the responsibility of the user to ensure that the issue is current. This information given is a non-controlled document</i></p>	