

HiChem Paint Technologies Pty Ltd

A.B.N. 95 064 139 653

73 Hallam South Road, HALLAM, VICTORIA 3803.

Telephone : {03} 9796 3400

Facsimile : {03} 9796 4500

Email: msdsinfo@hichem.com.auWebsite: www.hichem.com.au**IDENTIFICATION of the SUBSTANCE(S) and COMPOSITION**

Product Name	RAPID ENAMEL – LEAD CONTAINING COLOURS		RE – PBC
Product Use	Fast dry industrial spray enamel.		
Ingredients	Name	CAS Number	Proportion w/w
	Lead Chromate {as Lead}	7758 – 97 – 6	0.1 – 30 %
	Lead Chromate {as Chromium}	7758 – 97 – 6	0.1 – 10 %
	Toluene	108 – 88 – 3	10 – 30 %
	Xylene	1330 – 20 – 7	10 – 30 %
	Liquid Aliphatic Hydrocarbons – Low Flash Pt.	Not Known	10 – 30 %
	Synthetic Resins (Non–Hazardous)	Not Known	10 – 30 %
	Additives (Non–Hazardous)	Not Known	1 – 10 %

HAZARD IDENTIFICATION

The product is classified both as Hazardous Substance and Dangerous Goods in accordance to NOHSC.

Chronic Risk 33,40,60, 61,65,66,67 Danger of cumulative effects. Limited evidence of a carcinogenic effect. May impair fertility. May cause harm to unborn child. Harmful. May cause lung damage if swallowed. Repeated exposure may cause skin dryness and cracking. Vapours may cause headaches, drowsiness and dizziness.

Acute

Skin Risk 21,38 Harmful X_n, Irritant X_i
 Inhalation Risk 20,37 Harmful X_n Irritant X_i
 Ingestion Risk 22 Harmful X_n
 Eyes Risk 36 Irritant X_i

Safety Phrases 7/9,23.5,24/25,36/37/38/39 Further description, refer to page 4.

ADG PAINT– immiscible in water, UN 1263, Class 3, Packing Group II,

Classification HAZCHEM 3[**Y**]E.

SUSDP Classified as a Schedule S 6 poison.

Classification

FIRST AID MEASURES

<i>Inhalation</i>	If the applicator feels drowsy, dizzy, tired or experiencing headaches, remove the victim to the fresh air. Keep the victim warm and quiet until all symptoms subside.
<i>Ingestion</i>	If swallowed and only if the person is conscious, give water to drink. DO NOT induce vomiting. Seek URGENT medical attention if frothing from the mouth occurs.
<i>Eyes</i>	If splashed into eyes, hold eyes open, irrigate copiously with clean water for at least 15 minutes. Seek immediate medical attention if any irritation occurs.
<i>Skin</i>	If skin contact occurs, remove contaminated clothing, and wash thoroughly with soap and plenty of water. Seek medical attention if any irritation occurs.
<i>First Aid Facilities</i>	Clean Water Supply, soap or skin cleaner, barrier cream, emergency showers and eye wash stations.
<i>Advice to Doctor</i> S 45	If poisoning occurs, consult with the Poisons Information Centre {Telephone 13 11 26 }. Have a copy of this material safety data sheet or label available. Treat symptomatically.



FIRE FIGHTING MEASURES

<i>Extinguishing Media and Requirements</i>	Carbon Dioxide {CO ₂ }, alcohol resistant foam, dry chemical or water spray. DO NOT use water jets. Bund area with sand to prevent run – off entering waterways and drains.
<i>Fire Fighting Procedures & Precautions</i>	Fire – fighters should wear Chemical Splash Suit with attached Self – Contained Breathing Apparatus and gloves. Evacuate all non fire–fighting personnel away from the area. Turn off all electricity and power supplies. Keep containers cool with water spray or water to prevent rupture or burning. Move away all containers and equipment from the direction of the fire, if safe to do so. Keep upwind.
<i>Flammability</i>	Highly Flammable Liquid. Flash Point = – 1 °C
<i>Hazardous Decomposition Products</i>	On heating, containers may rupture and explode: contents may burn rapidly forming toxic gases including carbon monoxide.



ACCIDENTAL RELEASE MEASUREMENTS

<i>Spills and Leaks</i>	Contain all spills and leaks. Avoid contamination with spilt material on surfaces. Remove all sources of ignition and NO SMOKING . Wear the recommended full body impervious clothing, gloves and breathing apparatus as per AS– NZ 1715/16. Keep upwind. Absorb all spilt contents onto sand or earth.
<i>Disposal</i>	Collect all residues into labelled and sealed containers for disposal via special waste collection services as per local Statutory Authority requirements.
<i>Other Precautions</i>	Avoid contaminating waterways, drains, water courses and sewage.



HANDLING and STORAGE**Handling**

Keep out of reach of children. Avoid unnecessary contact with the material. After use before eating, drinking or smoking wash all exposed skin with soap and water.

Storage

Containers must be clearly labelled, rigid and strong. Store upright in a cool, dry, well ventilated area from heat, ignition sources and direct sunlight e.g. Flammable Goods Store as per AS 1940 requirements.

EXPOSURE CONTROLS**Exposure**

Toluene = 190 mg/m³.

Xylene = 350 mg/m³.

Standards MAK

Liquid Aliphatic Hydrocarbons – Low Flash Point = Not Known

Lead = 0.15 mg/m³.

Chromium = 0.05 mg/m³.

Engineering

When applying by spray, all work must be performed out in approved spray booth in accordance with Australian Standards.

Controls**PERSONAL PROTECTION****Inhalation**

AS –NZE 1715/16

The wearing of an Organic Vapour – Particulate Respirator **should** be worn at all times during the mixing and spray application period; until all spray mists are efficiently dispersed from the spray booth atmosphere before exiting.

Eye

AS –NZE 1337

The wearing of safety glasses fitted with side shields is recommended during the mixing and spray application period. Do not wear contact lenses.

Gloves

AS –NZE 2161

The wearing of Viton or PVC gloves is recommended during the mixing and spray application period.

Footwear

AS –NZE 2210

The wearing of enclosed footwear is recommended during the mixing and spray application period

Clothing

AS –NZE 2919

The wearing of anti-static clothing made on natural or synthetic high temperature fibre is recommended during the mixing and spray application period

Hearing


AS –NZE 1270

The wearing of hearing protection when applying by conventional spray is recommended during the spraying application period

Other

Requirements

Avoid contact with eyes and skin. Avoid inhaling spray mists and vapours.

**PHYSICAL – CHEMICAL PROPERTIES****Appearance**

A coloured liquid with a mild odour.

pH

Not required.

Vapour Pressure

Greater than 1.

(Butyl Acetate = 1)

Boiling Point °C

100 – 175 °C {literature value}

Density

1.1 – 1.3 {depending on colour}

Solubility in water

Immiscible

Flash Point °C

– 1 °C {literature value}

Flammability

Lower Explosive Limit = 1.0 %

Upper Explosive Limit = 7.5 %

Limits**Auto Ignition °C**

250 °C {literature value}

Volatile

Organic Solvents

Components

STABILITY and REACTIVITY

Chemical Stability	Stable under normal conditions of use.
Conditions to avoid	Avoid contact with heat and all ignition sources.
Incompatible materials	Incompatible with strong oxidizing agents
Hazardous decomposition products	On heating, containers may rupture and explode: contents may burn rapidly forming toxic gases including carbon monoxide and lead fumes.
Hazardous Reactions	Will not polymerize.

TOXICOLOGICAL INFORMATION

Inhalation	LC ₅₀	rat	Organic Solvents > 20mg/Litre for 4 hours
Skin	LD ₅₀	rabbit	Organic Solvents > 400 mg/kilogram bodyweight/day
Ingestion	LD ₅₀	rat	Organic Solvents and Lead Chromate > 200 mg/kilogram bodyweight/day
Eyes & Skin			Organic Solvents – irritant
Sensitization			No data for organic solvents.
Health Effects			R33 – Danger of cumulative effects R40 – Limited evidence of a carcinogenic effect. R60 – May impair fertility. R61 – May cause harm to unborn child.

ECOLOGICAL INFORMATION

Environment	R50 – Very toxic to aquatic organisms. R53 – May cause long – term adverse effects to the aquatic environment
--------------------	--

**DISPOSAL CONSIDERATIONS**

Collect all residues and placed into labelled and sealed containers. Do not incinerate empty containers after use. Dampen all unwanted cloths and rags in water prior to disposal. Do not recycle contents or spent containers. Crush all small empty containers. Larger containers and drums may be sent to an approved drum recycler. Ensure all contents do not pollute waterways, drains and other water courses.

TRANSPORT INFORMATION

UN number	1263		
Proper Shipping Name	PAINT, immiscible in water		
Class	3	Subsidiary Risk	Not Required
Packing Group	II		
Emergency Procedures	EP 3300	Initial Emergency Response Guide	14
HAZCHEM	3[Y]E		
IMDG			



REGULATORY INFORMATION

Risk Phrases R	33,40,60,61 65,66,67	Danger of cumulative effects. Limited evidence of a carcinogenic effect. May impair infertility. May cause harm to the unborn child. Harmful. May cause lung damage if swallowed. Repeated exposure may cause skin dryness and cracking. Vapours may cause headaches, drowsiness and dizziness
	20/21/22	Harmful by inhalation, skin contact and if swallowed.
	36/37/38	Irritating to eyes, respiratory tract and skin.
	11	Highly Flammable
Safety Phrases S	7/9	Keep containers closed and in a well ventilated area when not in use.
	23.5	Avoid breathing vapours or spray mist.
	24/25	Avoid contact with skin and eyes.
	36/37/38/39	Wear recommended Personal Protective Equipment – protective clothing, gloves, boots, respirator, eyes and hearing protection.
SUSDP Classification	Classified as a Schedule S 6 Poison. Contains maximum 30 % Lead and 10 % Chromium of the Non – Volatile Content of the paint.	

OTHER INFORMATION

Emergency Contact **Poisons Information Centre 13 11 26** **HiChem Paint Technologies (03) 9796 3400**

Disclaimer *Data provided is to best of HiChem Paint Technologies Proprietary Limited knowledge and believe to be accurate and reliable as of the date of issued. However no expressed or implied warranties are given. HiChem Paint Technologies Proprietary Limited cannot anticipate or control the conditions under which this information may be used. Therefore, it is user's responsibility to satisfy themselves as to the suitability and completeness of such information for their particular use. It is the responsibility of the user to ensure that the issue is current. This information given is a non-controlled document*