

HiChem Paint Technologies Pty.Ltd.

A.B.N. 95 064 139 563

73 Hallam South Road, HALLAM, VICTORIA 3803.

Telephone : {03} 9796 3400

Facsimile : {03} 9796 4500

Email: msdsinfo@hichem.com.auwww.hichem.com.au**HAZARD IDENTIFICATION**

The product is classified as both **Dangerous Goods** and **Hazardous Substance** in accordance to Work Safe Australia criteria.

Risk Phrases R

- 10 Flammable Liquid.
 20/21/22 Harmful by inhalation, contact with skin and if swallowed.
 36/37/38 Irritating to the eyes, respiratory system and skin.
 40 Limited evidence of a carcinogenic effect.
 52/53/59 Harmful to aquatic organisms and may cause long term adverse effects in the aquatic environment. Dangerous to the ozone layer.
 65/66/67 Harmful. May cause lung damage if swallowed. Repeated or prolonged exposure may cause skin dryness and cracking Vapours may cause headaches, drowsiness and dizziness.

Safety Phrases S

- 2 Keep out of reach of children
 7/9 Keep containers tightly closed when not in use and also in a well ventilated area.
 15/16 Keep away from heat and sources of ignition.
 20/21 When using, do not eat, drink or smoke.
 23.5 Do not breathe the vapours or spray mists.
 24/25 Avoid skin contact and with the eyes.
 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
 27 Take off immediately all contaminated clothing.
 28.1 In contact with the skin, wash immediately soap and plenty of water.
 36/37/38/39 Wear protective clothing, including enclosed footwear, PVC or Neoprene gloves, organic vapour respirator including eye, hair and face protection, and hearing protection.
 45 In case of accident, or if you feel unwell, seek medical advice immediately. Show the label where possible.
 62 If swallowed, do not induce vomiting: seek medical advice immediately. Show the label where possible.

ADG PAINT RELATED MATERIAL – THINNERS, immiscible in water, UN 1263,
Classification HAZCHEM 3[Y], Packing Group III, Initial Emergency Response Guide 15.Class 3.
SUSDP Classified as a Schedule S 5 poison.

IDENTIFICATION of the SUBSTANCE(S) and COMPOSITION

Product Name	SPECIAL THINNER 274	Code	SP 274
Product Use	A blend of organic solvents is used for thinning recommended products.		
Ingredients	Name	CAS Number	Proportion w/w
	Butyl Acetate	123 – 86 – 4	30 – 60.0 %
	Xylene	1330 – 20 – 7	10 – <30.0 %
	Ethyl Benzene	100 – 41 – 4	1.0 – <10.0 %
	Propylene Glycol Mono Methyl Ether Acetate	108 – 65 – 6	10 – <30.0 %

FIRST AID MEASURES


Inhalation	If the applicator feels drowsy, dizzy, tired or experiencing headaches, remove the victim away from the contaminated area to the fresh air. Keep the victim warm and quiet until all symptoms subside. If the victim is not breathing, apply artificial respiration immediately away from the contaminated area.
Ingestion	If swallow, and only if the person is conscious, give water to drink. DO NOT induced vomiting; seek URGENT medical attention if frothing from the mouth occurs.
Eyes	If splashed into eyes, hold eyelids apart, and flush the eyes continuously with running for at least 15 minutes. Continue flushing until advised by a doctor.
Skin and Hair	If skin and hair contact occurs, remove contaminated clothing, and wash thoroughly with soap and plenty of water. Continue flushing until advised by a doctor.
First Aid Facilities	Clean Water Supply, soap or skin cleaner, barrier cream, emergency showers and eye wash stations.
Advice to Doctor	If poisoning occurs, consult with the Poisons Information Centre {Telephone 13 11 26 }. Have a copy of this material safety data sheet or label available. Treat symptomatically as symptoms may be delayed for several hours after exposure.

**FIRE FIGHTING MEASURES**

Extinguishing Media and Requirements	Carbon Dioxide {CO ₂ }, alcohol resistant foam, dry chemical or water spray. DO NOT use water jets. Bund area with sand to prevent run – off entering waterways, sewage and drains.
Hazardous Decomposition Products	On heating, containers may rupture and explode: contents may burn rapidly forming toxic gases including carbon monoxide, soot and smoke, above the boiling point
Flammability	Flammable Liquid. Flash Point = 23 °C
Specific Hazards	Vapours may form explosive/air mixtures.
Precautions in connection with Fire	Fire – fighters should wear Chemical Splash Suit with attached Self – Contained Breathing Apparatus and gloves. Evacuate all non fire–fighting personnel away from the area. Turn off all electricity and power supplies. Keep containers cool with water spray or water to prevent rupture or burning. Move away all packages and equipment from the direction of the fire, if safe to do so. Keep upwind.

**ACCIDENTAL RELEASE MEASURES**

Emergency Procedures. Spills and Leaks	Contain all spills and leaks. Avoid contamination with spilt material on surfaces or entering waterways, drains and sewage. Remove all sources of ignition and NO SMOKING . Wear the recommended full body impervious clothing, gloves and breathing apparatus as per AS– NZ 1715/16. Keep upwind. Absorb all spilt contents onto sand or earth.
Disposal	Collect all residues into labelled and sealed containers for disposal via special waste collection services as per local Statutory Authority requirements.
Other Precautions	Ensure there is adequate ventilation at all times during the cleaning up period.



HANDLING and STORAGE**Precautions for Safe Handling**

Flammable Liquid. Remove all sources of ignition. Wear the recommended Personal Protective Equipment including organic vapour respirator, eye/face protection, protective clothing, gloves and enclosed footwear. Ensure there is adequate ventilation at all times. After use, before eating, drinking or smoking, wash all exposed skin and hair with soap and water.

Conditions of Safe Storage

Containers must be clearly labelled, rigid and strong. Store upright in a cool, dry, well ventilated area from heat, ignition sources and direct sunlight e.g. Flammable Goods Store as per AS 1940 requirements.

EXPOSURE CONTROLS**Exposure Standards MAK**

Propylene Glycol Mono Methyl Ether Acetate = 270 mg/m³.
Butyl Acetate = 480 mg/m³. Xylene = 350 mg/m³.
Ethyl Benzene = 440 mg/m³.

Exposure Standards STEL

Xylene = 655 mg/m³.

Biological Limited Values

There are no known Biological Limited Values have been assigned.

Engineering Controls

The use of local exhaust ventilation equipment is required. All ventilation equipment must be fitted with flame and explosion proof electrical fittings.

PERSONAL PROTECTION**Inhalation AS –Nzs 1715/16**

The wearing of Organic Vapour Respirator **should** be worn at all times during the handling and application period.

Eye AS –Nzs 1337

The wearing of safety glasses fitted with side shields **should** be worn at all times during the handling and application period. Do not wear contact lenses.

Gloves AS –Nzs 2161

The wearing of Neoprene or PVC gloves **should** be worn at all times during the handling and application period.

Footwear AS –Nzs 2210

The wearing of enclosed footwear **should** be worn at all times during the handling and application period.

Clothing AS –Nzs 2919


The wearing of anti-static clothing made on natural or synthetic high temperature fibre **should** be worn at all times during the handling and application period

Hearing AS –Nzs 1270

Not required.

Other Requirements

Avoid contact with eyes and skin. Avoid inhaling vapours and spray mists.



PHYSICAL – CHEMICAL PROPERTIES

Appearance	A colourless liquid with a strong odour.	
pH	Not required.	
Vapour Pressure (Butyl Acetate = 1)	Less than 1	
Boiling Point °C	127 – 145 °C (literature value)	
Density	0.90 {calculated value}	
Solubility in water	Immiscible	
Flash Point °C	23 °C (literature value)	
Flammability	Lower Explosive Limit = 1.0	Upper Explosive Limit = 10.8
Limits		
Auto Ignition °C	465 °C (literature value)	
Volatile	Liquid hydrocarbons and esters.	
Components		

STABILITY and REACTIVITY

Chemical Stability	Stable under normal conditions of use.
Conditions to avoid	Avoid contact with heat and all ignition sources.
Hazardous decomposition products	On heating, containers may rupture and explode: contents may burn rapidly forming toxic gases including carbon monoxide, soot and smoke.
Incompatible materials	Incompatible with strong oxidizing agents
Hazardous Reactions	Will not polymerize.

TOXICOLOGICAL INFORMATION

<i>Health Effects</i>	<i>Risk Phrase</i>	<i>Xylene</i>	<i>Butyl Acetate</i>	<i>Ethyl Benzene</i>	<i>Propylene Glycol Mono Methyl Acetate</i>
Inhalation	20	20 mgm/L.	20 mgm/L.	20	20 mgm/L
LC ₅₀ rat				mgm/L	
Dermal	21	4500	14400	2000	7500
LD ₅₀ rabbit		mgm/kg	mgm/kg	mgm/kg	mgm/kg
Oral	22	4300	10700	2000	8530
LD ₅₀ rat		mgm/kg	mgm/kg	mgm/kg	mgm/kg

Acute Oral Toxicity rat	Low toxicity. Aspiration into lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.
Acute Dermal Toxicity rabbit	Low toxicity.
Acute Inhalation Toxicity rat	Low toxicity. High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea; continued inhalation may result in unconsciousness and/or death.

TOXICOLOGICAL INFORMATION (CONTINUED)**Health Effects**

Inhalation	The inhalation of vapours may cause acute irritation to the respiratory system. Other symptoms may cause central nervous system depression resulting in headaches, dizziness, nausea, loss of co-ordination, impaired judgement. Vapours may cause headaches, drowsiness and dizziness
Ingestion	Large quantities may cause nausea and vomiting. Harmful. May cause lung damage if swallowed.
Eyes	May irritate to the eyes, including burning sensation, redness, swelling and/or blurred vision. Also, may cause decreased in colour perception.
Skin	May have degreasing effect on the skin may result in contact dermatitis. Repeated or prolonged exposure may cause skin dryness and cracking.
Carcinogenic	Limited evidence of a carcinogenic effect
Mutagenic	Not mutagenic in animal studies.
Reproductive	No data available
Toxicity	

ECOLOGICAL INFORMATION

Environment	Harmful to aquatic organisms (R 52) May cause long – term adverse effects in the aquatic environment (R 53). Dangerous to the ozone layer (R 59).
Persistence/ Degradability	No data available.
Mobility	No data available
Environment Protection	Not Known

**DISPOSAL CONSIDERATIONS**

Collect all residues and placed into labelled and sealed containers. Do not incinerate empty containers after use. Dampen all unwanted cloths and rags in water prior to disposal. Do not recycle contents. Crush all small empty containers. Large containers and drums may be sent to an approved drum recycler. Ensure all contents do not pollute waterways, drains and sewage.

TRANSPORT INFORMATION

UN number	1263		
Proper Shipping Name	PAINT RELATED MATERIAL –THINNERS, N.O.S., immiscible in water.		
Class	3	Subsidiary Risk	Not Required
Packing Group	III		
Emergency Procedures	EP 3305	Initial Emergency Response Guide	15
HAZCHEM	3[Y]		
IMDG	Not Known		



REGULATORY INFORMATION**Regulatory
Information and
Hazard Category
SUSDP
Classification**

The product is classified as a Hazardous Substance in accordance to Work Safe Australia as Harmful and Irritant.

Classified as a Schedule S 5 Poison.

OTHER INFORMATION**Emergency
Contact
Disclaimer**

Poisons Information Centre 13 11 26

HiChem Paint Technologies
(03) 9796 3400

Data provided is to best of HiChem Paint Technologies Proprietary Limited knowledge and believe to be accurate and reliable as of the date of issued. However no expressed or implied warranties are given. HiChem Paint Technologies Proprietary Limited cannot anticipate or control the conditions under which this information may be used. Therefore, it is user's responsibility to satisfy themselves as to the suitability and completeness of such information for their particular use. It is the responsibility of the user to ensure that the issue is current. This information given is a non-controlled document



Version 2.0
HIGH 7526
November 2011