

**HiChem Paint Technologies Pty.Ltd.**

A.B.N. 95 064 139 653

73 Hallam South Road, HALLAM, VICTORIA 3803.

Telephone : {03} 9796 3400

Facsimile : {03} 9796 4500

Email:msdsinfo@hichem.com.au www:hichem.com.au

**IDENTIFICATION of the SUBSTANCE(S) and COMPOSITION**

<i>Product Name</i>	SPRAY PUTTY – AEROSOL		<i>Code</i>
<i>Product Use</i>	An aerosol spray used for “touch-up” or repair work of small automotive surfaces.		
<i>Ingredients</i>	<i>Name</i>	<i>CAS Number</i>	<i>Proportion w/w</i>
	Toluene	108 – 88 – 3	1.0 – <10 %
	Xylene	1330 – 20 – 7	1.0 – <10 %
	Ethyl Benzene	100 – 41 – 4	1.0 – <10 %
	Di Methyl Ether	115 – 10 – 6	30 – 60 %
	Encapsulated Crystalline Silicon Dioxide	14808 – 60 – 7	0.1 – <1.0 %
	Coloured Pigments/Extenders (non-hazardous)	Mixture	10 – <30 %
	Synthetic Resins (non-hazardous)	Proprietary	10 – <30 %
	Aliphatic Alcohols	Mixture	1.0 – <10 %
	Acetone	67 – 64 – 1	10 – <30 %
	Aliphatic Esters	Mixture	1.0 – <10 %
	Additives (non-hazardous)	Mixture	1.0 – <10 %

**HAZARD IDENTIFICATION**

The product is classified as both **Dangerous Goods and Hazardous Substance** in accordance to ASCC

**Risk Phrases R**

- 12 Extremely Flammable Gas
- 21/22 Harmful in contact with the skin and if swallowed.
- 40 Limited evidence of a carcinogenic effect
- 48/20 Danger of serious damage to health by prolonged exposure through inhalation.
- 36/38 Irritating to the eyes and skin.
- 51/53/59 Toxic to aquatic organisms and may cause long term adverse effects in the aquatic environment. Dangerous for the ozone layer.
- 63 Causes foetotoxicity in animals at doses which are maternally toxic.
- 65/66/67 Harmful. May cause lung damage if swallowed. Repeated or prolonged exposure may cause skin dryness and cracking. Vapours may cause headaches, drowsiness and dizziness.

**Safety Phrases S**

- 2 Keep out of reach of children.
- 7/9 Keep containers tightly closed when not in use and also in a well ventilated area.
- 15 Keep away from heat.
- 16/33 Keep away from sources of ignition. Take precautionary measures against static electricity.
- 20/21 When using, do not eat, drink or smoke.
- 23.2 Do not breathe vapours.
- 24/25 Avoid skin contact and with the eyes.
- 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- 27 Take off immediately all contaminated clothing.
- 28.1 In contact with the skin, wash immediately soap and plenty of water.
- 36/37/38/39 The wearing of an Organic Vapour Respirator, Safety Glasses fitted with side – shields, Viton or PVC gloves, enclosed footwear, high temperature and anti – static clothing.
- 45 In case of accident, or if you feel unwell, seek medical advice immediately. Show the label where possible.
- 62 If swallowed, do not induce vomiting: seek medical advice immediately. Show the label where possible.

**HAZARD IDENTIFICATION (continued)**

The product is classified as both **Dangerous Goods and Hazardous Substance** in accordance to ASCC

**ADG Classification** AEROSOLS – with a capacity less than 1 Litre, UN 1950, HAZCHEM 2 Y, Class 3.

**SUSDP** Classified as a Schedule S 5 poison

**FIRST AID MEASURES**

<b>Inhalation</b>	If the applicator feels drowsy, dizzy, tired or experiencing headaches, remove the victim to the fresh air. Keep the victim warm and quiet until all symptoms subside.
<b>Ingestion</b>	Unlikely route of exposure. Give 2 glasses of clean water to drink. If any symptoms occur, <b>DO NOT</b> induce vomiting; seek URGENT medical attention if frothing from the mouth occurs.
<b>Eyes</b>	If splashed into eyes, hold eyes open, irrigate copiously with clean water for at least 15 minutes. Seek immediate medical attention if any irritation occurs.
<b>Skin</b>	If skin contact occurs, remove contaminated clothing, and wash thoroughly with soap and plenty of water. Seek medical attention if any irritation occurs.
<b>First Aid Facilities</b>	Clean Water Supply, soap or skin cleaner, barrier cream, emergency showers and eye wash stations.
<b>Advice to Doctor</b>	If poisoning occurs, consult with the Poisons Information Centre {Telephone <b>13 11 26</b> }. Have a copy of this material safety data sheet or label available. Treat symptomatically as systems may be delayed for several hours after exposure.

**FIRE FIGHTING MEASURES**

<b>Extinguishing Media and Requirements</b>	Carbon Dioxide {CO <sub>2</sub> }, alcohol resistant foam, dry chemical or water spray. <b>DO NOT</b> use water jets. Bund area with sand to prevent run – off entering waterways and drains.
<b>Fire Fighting Procedures &amp; Precautions</b>	Fire – fighters <b>must</b> wear Chemical Splash Suit with attached Self – Contained Breathing Apparatus and gloves. Evacuate all non fire–fighting personnel away from the area. Turn off all electricity and power supplies. Keep containers cool with water spray or water to prevent rupture or burning. Move away all containers and equipment from the direction of the fire, if safe to do so. Keep upwind.
<b>Flammability</b>	Extremely Flammable Gas. Flash Point = < - 25 °C
<b>Hazardous Decomposition Products</b>	On heating, containers may rupture and explode: contents may burn rapidly forming toxic gases including carbon monoxide



## ACCIDENTAL RELEASE MEASURES

<b>Spills and Leaks</b>	Contain all spills and leaks. Avoid contamination with spilt material on surfaces. Remove all sources of ignition and <b>NO SMOKING</b> . Wear the recommended full body impervious clothing, gloves and breathing apparatus as per AS– NZ 1715/16. Keep upwind. Absorb all spilt contents onto sand or earth.
<b>Disposal</b>	Collect all residues into labelled and sealed containers for disposal via special waste collection services as per local Statutory Authority requirements.
<b>Other Precautions</b>	Avoid contaminating waterways, drains, water courses and sewage.



## HANDLING and STORAGE


<b>Handling</b>	Keep out of reach of children. Avoid unnecessary contact with the material. After use before eating, drinking or smoking wash all exposed skin with soap and water.
<b>Storage</b>	Containers must be clearly labelled, rigid and strong. Store upright in a cool, dry, well ventilated area from heat, ignition sources and direct sunlight e.g. Flammable Goods Store as per AS 1940 requirements.

## EXPOSURE CONTROLS

<b>Exposure Standards MAK</b>	Di Methyl Ether = Not Known	Ethyl Benzene = 440 mg/m <sup>3</sup> .
<b>Exposure Standards STEL</b>	Toluene = 190 mg/m <sup>3</sup> .	Xylene = 350 mg/m <sup>3</sup>
<b>Engineering Controls</b>	Toluene = 565 mg/m <sup>3</sup> .	Xylene = 655 mg/m <sup>3</sup> .
	During the spray application period, ensure there is adequate ventilation at all times e.g. preferably with doors and windows open. Do not use in a confined space.	

## PERSONAL PROTECTION

<b>Inhalation AS –Nzs 1715/16</b>	The wearing of an Organic Vapour Respirator <b>must be</b> worn at all times during the application period..
<b>Eye AS –Nzs 1337</b>	The wearing of safety glasses fitted with side shields <b>must be</b> worn during the application period. Do not wear contact lenses.
<b>Gloves AS –Nzs 2161</b>	The wearing of Viton or PVC gloves <b>must be</b> worn during the application period.
<b>Footwear AS –Nzs 2210</b>	The wearing of enclosed footwear <b>must be</b> worn during the application period.
<b>Clothing AS –Nzs 2919</b>	The wearing of anti–static clothing made on natural or synthetic high temperature fibre <b>must be</b> worn during the application period.
<b>Hearing AS –Nzs 1270</b>	Not required.
<b>Other Requirements</b>	Avoid contact with eyes and skin. Avoid inhaling vapours at all times.



**PHYSICAL – CHEMICAL PROPERTIES**

<b>Appearance</b>	A coloured gas with a strong odour.	
<b>pH</b>	Not required.	
<b>Vapour Pressure</b> (Butyl Acetate = 1)	Greater than 1.0	
<b>Boiling Point °C</b>	Not Known	
<b>Density</b>	0.86 {calculated value}	
<b>Solubility in water</b>	Immiscible	
<b>Flash Point °C</b>	< - 25 °C {literature value}	
<b>Flammability Limits</b>	Lower Explosive Limit = 1.0 %	Upper Explosive Limit = 15.0 %
<b>Auto Ignition °C</b>	250 °C {literature value}	
<b>Volatile Components</b>	Organic Solvents.	

**STABILITY and REACTIVITY**

<b>Chemical Stability</b>	Stable under normal conditions of use.
<b>Conditions to avoid</b>	Avoid contact with heat and all ignition sources.
<b>Hazardous decomposition products</b>	On heating, containers may rupture and explode: contents may burn rapidly forming toxic gases including carbon monoxide.
<b>Incompatible materials</b>	Incompatible with strong oxidizing agents
<b>Hazardous Reactions</b>	Will not polymerize.

**TOXICOLOGICAL INFORMATION**

<i>Health Effects</i>	<i>Risk Phrase</i>	<i>Ethyl Benzene</i>	<i>Xylene</i>	<i>Toluene</i>
Inhalation LC <sub>50</sub> rat	20	>20 mgm/L	>20 mgm/L	>20 mgm/L
Dermal LD <sub>50</sub> rabbit	21	>2000mgm/kg	>2000mgm/kg	>2000mgm/kg
Oral LD <sub>50</sub> rat	22	>2000mgm/kg	>2000mgm/kg	640 mgm/kg

**Note**

Risk phrases R20/21/22 has been assigned by the EEC Council Directive 67/548/EEC.

Risk Phrases R20/21/22 – Harmful by inhalation, skin contact or if swallowed.

Acute Oral Toxicity rat	Low toxicity. Aspiration into lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.
Acute Dermal Toxicity rabbit	Low toxicity
Acute Inhalation Toxicity rat	Low toxicity. High concentrations may cause central nervous system depression resulting in headaches, dizziness, nausea, loss of co-ordination and impaired judgement: continued inhalation may result in unconsciousness and/or death.

**OTHER TOXICOLOGICAL INFORMATION (continued)****Health Effects**

Inhalation	Other symptoms may cause dizziness, nausea, coughing, lack of co-ordination and impair judgement.
Ingestion	Large quantities may cause nausea and vomiting.
Eyes	Irritating to the eyes, including burning sensation, redness, swelling and/or blurred vision.
Skin	Will have degreasing effect on the skin may result in contact dermatitis.
Carcinogenicity	Limited evidence of a carcinogenic effect.
Mutagenicity	Not mutagenic in animal studies
Reproductive Toxicity	Causes foetotoxicity in animals at doses which are maternally toxic. Does not impair fertility.

**ECOLOGICAL INFORMATION**

<b>Environment</b>	Toxic to aquatic organisms (R51). May cause long-term adverse effects in the aquatic environment (R53). Dangerous for the ozone layer (R59).
--------------------	--

**DISPOSAL CONSIDERATIONS**

Collect all residues and placed into labelled and sealed containers. Do not incinerate empty containers after use. Dampen all unwanted cloths and rags in water prior to disposal. Do not recycle contents or spent containers. Crush all small empty containers. Larger containers and drums may be sent to an approved drum recycler. Ensure all contents do not pollute waterways, drains and other water courses.

**TRANSPORT INFORMATION**

<b>UN number</b>	1950		
<b>Proper Shipping Name</b>	AEROSOLS, capacity less than 1 Litre		
<b>Class</b>	2.1	<b>Subsidiary Risk</b>	Not Required
<b>Packing Group</b>	Not Assigned		
<b>Emergency Procedures</b>	3900	<b>Initial Emergency Response Guide</b>	49
<b>HAZCHEM</b>	2 Y		
<b>IMDG</b>	Not Known		

**REGULATORY INFORMATION**

<b>SUSDP</b>	Classified as a Schedule S 5 poison.
--------------	--------------------------------------

**OTHER INFORMATION*****Emergency  
Contact  
Disclaimer*****Poisons Information Centre 13 11 26****HiChem Paint Technologies  
(03) 9796 3400**

*Data provided is to best of HiChem Paint Technologies Proprietary Limited knowledge and believe to be accurate and reliable as of the date of issued. However no expressed or implied warranties are given. HiChem Paint Technologies Proprietary Limited cannot anticipate or control the conditions under which this information may be used. Therefore, it is user's responsibility to satisfy themselves as to the suitability and completeness of such information for their particular use. It is the responsibility of the user to ensure that the issue is current. This information given is a non-controlled document*