

HiChem Industries Pty Ltd

A.B.N. 95 064 139 653

73 Hallam South Road, HALLAM, VICTORIA 3803.

Telephone : {03} 9796 3400

Facsimile : {03} 9796 4500

Email: msdsinfo@hichem.com.auWebsite: www.hichem.com.au**IDENTIFICATION of the SUBSTANCE(S) and COMPOSITION**

Product Name	WOOD STOP PUTTY	Code	WSP 600
Product Use	Use as an interior knifing filler for bare timber surfaces		
Ingredients	Name	CAS Number	Proportion w/w
	Crystalline Silicon Dioxide	14808-60-7	10 – 30 %
	Butyl Acetate	123-86-4	10 – 30 %
	Coloured Pigments / Extenders(Non-Hazardous)	Not Known	60 – 100 %
	Synthetic Resins (Non-Hazardous)	Not Known	1 – 10 %
	Additives (Non-Hazardous)	Not Known	1 – 10 %

HAZARD IDENTIFICATION

Chronic	Risk	65,66,67	Harmful. May cause lung damage if swallowed. Repeated exposure may cause skin dryness and cracking. Vapours may cause headaches, drowsiness and dizziness.
Acute			
Skin	Risk	21,38	Harmful X _n , Irritant X _i
Inhalation	Risk	20,37	Harmful X _n Irritant X _i
Ingestion	Risk	22	Harmful X _n
Eyes	Risk	36	Irritant X _i
ADG	PAINT RELATED MATERIAL – immiscible in water, UN 1263, Class 3, Packing		
Classification	Group II, HAZCHEM 3[Y]E.		
SUSDP	Classified as a Schedule S 5 poison.		
Classification			

FIRST AID MEASURES

Inhalation	If the applicator feels drowsy, dizzy, tired or experiencing headaches, remove the victim to the fresh air. Keep the victim warm and quiet until all symptoms subside.
Ingestion	If swallowed and only if the person is conscious, give water to drink. DO NOT induce vomiting. Seek URGENT medical attention if frothing from the mouth occurs.
Eyes	If splashed into eyes, hold eyes open, irrigate copiously with clean water for at least 15 minutes. Seek immediate medical attention if any irritation occurs.
Skin	If skin contact occurs, remove contaminated clothing, and wash thoroughly with soap and plenty of water. Seek medical attention if any irritation occurs.
First Aid Facilities	Clean Water Supply, soap or skin cleaner, barrier cream, emergency showers and eye wash stations.
Advice to Doctor	If poisoning occurs, consult with the Poisons Information Centre {Telephone 13 11 26 }. Have a copy of this material safety data sheet or label available. Treat symptomatically.



FIRE FIGHTING MEASURES

Extinguishing Media and Requirements Fire Fighting Procedures & Precautions

Carbon Dioxide {CO₂}, alcohol resistant foam, dry chemical or water spray. **DO NOT** use water jets. Bund area with sand to prevent run – off entering waterways and drains. Fire – fighters should wear Chemical Splash Suit with attached Self – Contained Breathing Apparatus and gloves. Evacuate all non fire–fighting personnel away from the area. Turn off all electricity and power supplies. Keep containers cool with water spray or water to prevent rupture or burning. Move away all containers and equipment from the direction of the fire, if safe to do so. Keep upwind.



Flammability Hazardous Decomposition Products

Highly Flammable Paste. Flash Point = 4°C
On heating, containers may rupture and explode: contents may burn rapidly forming toxic gases including carbon monoxide and oxides of nitrogen.

ACCIDENTAL RELEASE MEASURES

Spills and Leaks

Contain all spills and leaks. Avoid contamination with spilt material on surfaces. Remove all sources of ignition and **NO SMOKING**. Wear the recommended full body impervious clothing, gloves and breathing apparatus as per AS– NZ 1715/16. Keep upwind. Absorb all spilt contents onto sand or earth.



Disposal

Collect all residues into labelled and sealed containers for disposal via special waste collection services as per local Statutory Authority requirements.

Other Precautions

Avoid contaminating waterways, drains, water courses and sewage.

HANDLING and STORAGE

Handling

Keep out of reach of children. Avoid unnecessary contact with the material. After use before eating, drinking or smoking wash all exposed skin with soap and water.

Storage

Containers must be clearly labelled, rigid and strong. Store upright in a cool, dry, well ventilated area from heat, ignition sources and direct sunlight e.g. Flammable Goods Store as per AS 1940 requirements.

EXPOSURE CONTROLS

Exposure Standards MAK Engineering Controls

Crystalline Silicon Dioxide = 0.1 mg/m³. Butyl Acetate = 480 mg/ m³.

When applying the product, ensure there is adequate ventilation during the application period.

PERSONAL PROTECTION

Inhalation
AS –N.ZS 1715/16
Eye
AS –N.ZS 1337

Gloves
AS –N.ZS 2161
Footwear
AS –N.ZS 2210
Clothing
AS –N.ZS 2919

Hearing
AS –N.ZS 1270
Other Requirements

It is advisable to wear an Organic Vapour Respirator is recommended during the application period..

It is advisable to wear safety glasses fitted with side shields recommended during the application period. Do not wear contact lenses.


It is advisable to wear Viton or PVC gloves recommended during the application period.

It is advisable to wear enclosed footwear is recommended during the application period

It is advisable to wear anti-static clothing made on natural or synthetic high temperature fibre is recommended during the application period

Not Required.

Avoid contact with eyes and skin. Wear the recommended Personal Protective Equipment as described.

**PHYSICAL – CHEMICAL PROPERTIES**

Appearance
pH
Vapour Pressure
(Butyl Acetate = 1)
Boiling Point °C
Density
Solubility in water
Flash Point °C
Flammability Limits
Auto Ignition °C
Volatile Components

A coloured paste with a sweet odour.

Not required.

Greater than 1.

111 – 128 °C {literature value}

1.8

Immiscible

4 °C {literature value}

Lower Explosive Limit = 1.0 %

Upper Explosive Limit = 7.0 %

370 °C {literature value}

Organic Solvents

STABILITY and REACTIVITY

Chemical Stability
Hazardous
Polymerization
Conditions to avoid
Incompatible materials
Hazardous decomposition products

Stable under normal conditions of use.

Will not polymerize.

Avoid contact heat and all ignition sources.

Incompatible with strong oxidizing agents

Stable.

TOXICOLOGICAL INFORMATION

Inhalation **LC₅₀** **rat** Organic Solvents > 20mg/Litre for 4 hours
Skin **LD₅₀** **rabbit** Organic Solvents > 400 mg/kilogram bodyweight/day
Ingestion **LD₅₀** **rat** Organic Solvents > 200 mg/kilogram bodyweight/day
Eyes
Sensitization No data for Organic Solvents – non sensitizer

ECOLOGICAL INFORMATION

Environment No data available.

DISPOSAL CONSIDERATIONS

Collect all residues and placed into labelled and sealed containers. Do not incinerate empty containers after use. Dampen all unwanted cloths and rags in water prior to disposal. Do not recycle contents or spent containers. Crush all small empty containers. Larger containers and drums may be sent to an approved drum recycler. Ensure all contents do not pollute waterways, drains and other water courses.

TRANSPORT INFORMATION

UN number	1263		
Proper Shipping Name	PAINT RELATED MATERIAL – FILLERS , immiscible in water		
Class	3	Subsidiary Risk	Not Required
Packing Group	II		
Emergency Procedures	EP 3300	Initial Emergency Response Guide	14
HAZCHEM	3[Y]E		
IMDG			

**REGULATORY INFORMATION**

Risk Phrases R	65,66,67	Harmful. May cause lung damage if swallowed. Repeated exposure may cause skin dryness and cracking. Vapours may cause headaches, drowsiness and dizziness
	20/21/22	Harmful by inhalation, skin contact and if swallowed.
	36/37/38	Irritating to eyes, respiratory system and skin.
	11	Highly Flammable
Safety Phrases S	7/9	Keep containers closed and in a well ventilated area when not in use.
	23.2	Avoid breathing vapours.
	24/25	Avoid contact with skin and eyes.
	36/37/38/39	Wear recommended Personal Protective Equipment – protective clothing, gloves, boots, respirator and eye and protection.
SUSDP Classification	The current product is labelled as Schedule 5 Poison.	

OTHER INFORMATION

Emergency Contact **Poisons Information Centre 13 11 26 HiChem Industries (03) 9796 3400**

Disclaimer Data provided is to best of HiChem Industries Proprietary Limited knowledge and believe to be accurate and reliable as of the date of issued. However no expressed or implied warranties are given. HiChem Industries Proprietary Limited cannot anticipate or control the conditions under which this information may be used. Therefore, it is user's responsibility to satisfy themselves as to the suitability and completeness of such information for their particular use. It is the responsibility of the user to ensure that the issue is current. This information given is a non-controlled document